

Entergy Nuclear Northeast Entergy Nuclear Operations, Inc. James A. Fitzpatrick NPP P.O. Box 110 Lycoming, NY 13093 Tel 315 349 6024 Fax 315 349 6480

Pete Dietrich Site Vice President - JAF

April 26, 2007 JAFP-07-0054

U.S. Nuclear Regulatory Commission ATTN: Document Control Desk Washington, D.C. 20555

SUBJECT:

James a. Fitzpatrick Nuclear Power Plant Docket No. 50-333, License No. DPR-59 Annual Radioactive Effluent Release Report

Gentlemen:

Attachment 1 is the Annual Radioactive Effluent Release Report for the period of January 1, 2006 through December 31, 2006. This report is submitted in accordance with the requirements of the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual, Part 1, Radiological Controls, Section 6.2.

This report includes, an assessment of the radiation doses to the public due to the radioactive liquid and gaseous effluents released during the 2006 calendar year. The format used for the effluent data is outlined in Appendix B of Regulatory Guide 1.21, Revision 1. Distribution is in accordance with Regulatory Guide 10.1, Revision 4 and 10 CFR 50.4.

If you have any questions concerning the attached report, please contact Crystal A. Boucher, Chemistry Superintendent, at the James A. FitzPatrick Nuclear Power Plant at (315)349-6748.

There are no commitments contained in this letter.

Pete Dietrich

Site Vice President

Very truly yours,

PD/CAB/jbh

Attachments: 1) James A. FitzPatrick Nuclear Power Plant Annual Radioactive Effluent Release Report

cc: Next Page

IE48

Mr. Samuel Collins
Regional Administrator, Region I
U. S. Nuclear Regulatory Commission
475 Allendale Road
King of Prussia, PA 19406-1415

cc:

Resident Inspector's Office U. S. Nuclear Regulatory Commission James A. FitzPatrick Nuclear Power Plant P.O. Box 136 Lycoming, NY 13093

Mr. John Boska
Plant Licensing Branch
Division of Operating Reactor Licensing
Office of Nuclear Reactor Regulation
U. S. Nuclear Regulatory Commission
Mail Stop O-8-C2
Washington D.C. 20555

Mr. Don Sherman American Nuclear Insurers 95 Glastonbury Boulevard Glastonbury, CT 06033-4438

Paul Merges, PhD Chief, Bureau of Radiation Division of Hazardous Substance Regulation New York State Department of Environmental Conservation Albany, NY 12233

- K. Mulligan (JAF)
- C. Faison (ENOC/WPO)
- J. McCann (ENOC/WPO)
- J. Furfaro (ENOC/WPO)
- W. Hamblin (CHEM/JAF)
- T. Kurtz (NMPC)

JAFP-07-0054 ATTACHMENT 1

ENTERGY NUCLEAR OPERATIONS, INC. JAMES A. FITZPATRICK NUCLEAR POWER PLANT ANNUAL RADIOACTIVE EFFLUENT RELEASE REPORT

JANUARY 1, 2006 - DECEMBER 31, 2006

DOCKET NO.: 50-333

LICENSE NO.: DPR-59

SUPPLEMENTAL INFORMATION

FACILITY: JAFNPP LICENSEE: ENTERGY NUCLEAR OPERATIONS, INC.

1. Offsite Dose Calculation Manual Part 1 Radiological Controls

- a. Fission and Activation Gases:
 - (1) The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluent shall be limited as follows:
 - (a) Less than or equal to 500 mrem/year to the whole body and less than or equal to 3000 mrem/year to the skin from noble gases.
 - (2) The air dose to areas at or beyond the site boundary from noble gases released from the plant in gaseous effluent shall be limited:
 - (a) During any calendar quarter, to less than or equal to 5 mrad from gamma radiation, and less than or equal to 10 mrad from beta radiation; and,
 - (b) During any calendar year, to less than or equal to 10 mrad from gamma radiation and less than or equal to 20 mrad from beta radiation.
- b. Tritium, Iodines and Particulates, Half Lives > 8 days:
 - (1) The dose to a member of the public at or beyond the site boundary from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days released from the plant in gaseous effluent shall be limited:
 - (a) During any calendar quarter to less than or equal to 7.5 mrem to any organ; and,
 - (b) During any calendar year to less than or equal to 15 mrem to any organ.
 - (c) Less than 0.1% of the limits of Specification 3.4.1.c.1.a and 3.4.1.c.1.b as a result of burning contaminated oil.
 - (2) The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluents shall be limited as follows:
 - (a) Less than or equal to 1500 mrem/year to any organ from Iodine-131, Iodine-133, Tritium and for radioactive materials in particulate form with half-lives greater than 8 days (inhalation pathway only).

SUPPLEMENTAL INFORMATION (continued)

c. Liquid Effluents:

- (1) The concentration of radioactive materials released to the unrestricted areas shall not exceed ten times the values specified in 10 CFR 20.1001-20.2402, Appendix B, Table 2, Column 2. For dissolved or entrained noble gases the concentration shall be limited to 2.00E-04 μCi/ml.
- (2) The dose to a member of the public from radioactive materials released from the plant in liquid effluents to unrestricted areas shall be limited as follows:
 - (a) During any calendar quarter, limited to less than or equal to 1.5 mrem to the whole body and to less than or equal to 5 mrem to any organ; and,
 - (b) During any calendar year, limited to less than or equal to 3 mrem to the whole body and to less than or equal to 10 mrem to any organ.

2. 10X Effluent Concentrations

	a.	Fission a	nd activation	gases:	None sr	pecified)
--	----	-----------	---------------	--------	---------	-----------

b. Iodines: (None specified)

c. Particulates, half-lives >8 days: (None specified)

d.	Liquid effluents:	Quarter 1	Quarter 2	Quarter 3	Quarter 4
	 Fission and activation products (mixture EC) (μCi/ml) 	None'	None	None	1.14E-04
	(2) Tritium (µCi/ml)	1.00E-02	1.00E-02	1.00E-02	1.00E-02
	(3) Dissolved and entrained gases (μCi/ml)	2.00E-04	2.00E-04	2.00E-04	2.00E-04

SUPPLEMENTAL INFORMATION (continued)

3. Average Energy

(None specified)

4. Measurements and Approximations of Total Radioactivity

- a. Fission and Activation Gases: Continuous monitor on each release path calibrated to a marinelli grab sample analyzed by gamma spectroscopy; bubbler grab sample analyzed for Tritium.
- b. Iodines: Gamma spectral analysis of charcoal cartridge and particulate filter on each release path.
- c. Particulates: Gamma spectral analysis of each particulate filter and charcoal cartridge for each release path. A four week per quarter composite of particulate filters for each release path for Strontium-89 and Strontium-90. One week per month particulate filter for each release path for gross alpha.
- d. Liquid Effluents: Gamma spectral analysis of each batch discharged, except composite analysis for Strontium-89, Strontium-90, Iron-55, Tritium, and Alpha.
- e. Solid Waste: Gamma spectral analysis of a representative sample of each waste shipment. Scaling factors established from off-site composite sample analyses to estimate concentration of non-gamma emitters. Low activity trash shipments, curie content estimated by dose rate measurement and application of appropriate scaling factors.
- f. Error Estimation Method: Overall error for sampling and analysis estimated by combining individual errors using error propagation methods. This process is composed of determinate and undeterminate errors.

Determinate - Pump flowrates, volume measurements and analysis collection yields Undeterminate - Random counting error estimated using accepted statistical calculations

SUPPLEMENTAL INFORMATION (continued)

5. Batch Releases

a. Liquid: Canal	Quarter 1	Quarter 2	Quarter 3	Quarter 4
(1) Number of batch releases:	2.00E+00	6.00E+00	4.00E+00	3.10E+01
(2) Total time period for batch release: (min)	1.01E+02	1.73E+02	1.55E+02	1.73E+03
(3) Maximum time period for batch release: (min)	6.50E+01	6.30E+01	7.00E+01	1.05E+02
(4) Average time period for batch release: (min)	5.05E+01	2.88E+01	3.89E+01	5.58E+01
(5) Minimum time period for batch release: (min)	3.60E+01	2.00E+00	3.00E+00	5.00E+00
(6) Total Activity Released (Ci)	3.94E-06	1.53E-04	2.28E-04	3.81E+00
(7) Total Volume Released (liters)	1.48E+03	6.35E+03	8.55E+03	8.68E+05
b. Liquid: Non-Canal				·
(1) Number of batch releases:	4.00E+00	1.20E+01	1.20E+01	1.20E+01
(2) Total time period for batch release: (min)	4.00E+00	3.36E+01	3.75E+02	1.72E+02
(3) Maximum time period for batch release: (min)	1.00E+00	1.40E+01	8.00E+01	1.11E+02
(4) Average time period for batch release: (min)	1.00E+00	2.80E+00	3.15E+01	1.43E+01
(5) Minimum time period for batch release: (min)	1.00E+00	1.00E+00	2.00E+00	1.00E+00
(6) Total Activity Released (Ci)	3.87E-06	2.64E-05	3.19E-04	8.79E-05
(7) Total Volume Released (liters)	1.82E+03	1.27E+04	1.42E+05	6.56E+04

SUPPLEMENTAL INFORMATION (continued)

c. Gaseous:

There were no gaseous batch releases for this report period.

6. Abnormal Releases

a.	Liquid:	Quarter 1	Quarter 2	Quarter 3	Quarter 4
	(1) Number of releases:(2) Total activity released:	NONE NONE	NONE NONE	NONE NONE	NONE NONE
b.	Gaseous				
	(1) Number of releases:(2) Total activity released:	NONE NONE	NONE NONE	NONE NONE	NONE NONE

TABLE 1A

GASEOUS EFFLUENTS--SUMMATION OF ALL RELEASES

			<u>UNIT</u>	OTR 1	OTR 2	OTR 3	OTR 4	EST TOTAL ERROR %
A.	FIS	SSION AND ACTIVATION GASES						
	1.	Total Release	Ci	4.14E+02	4.02E+02	3.87E+02	8.43E+01	≤2.50E+01
	 Average release rate for period Applicable ODCM Limit 	μCi/sec %	5.27E+01 *	5.11E+01 *	4.86E+01 *	1.06E+01 *		
В.	IOI	DINE-131						
	1.	Total lodine-131	Ci	5.80E-04	5.84E-04	3.97E-04	2.21E-03	≤2.50E+01
	2.	Average release rate for	C:/p.p.p	7 075 05	7 405 05	4 00E 0E	0.705.04	
	3.	period Applicable ODCM Limit	μCi/sec %	7.37E-05 *	7.43E-05 *	4.99E-05 *	2.78E-04 *	
•	TO A							
C.		RTICULATES	C:	4 005 04	6 605 04	5.93E-04	2.87E-04	≤3.60E+01
	1.	Particulates with half-lives >8 days	Ci	4.82E-04	6.60E-04	5.93E-04	2.07E-04	≥3.00€+01
	2.	Average release rate for period	μCi/sec	6.14E-05	8.39E-05	7.46E-05	3.61E-05	
	3.	Applicable ODCM Limit	%	*	*	*	*	
	4.	Gross alpha radioactivity	Ci	4.52E-07	1.26E-07	3.88E-07	4.60E-07	≤2.50E+01
D.	TR	ITIUM						
	1.	Total Release	Ci	3.99E+00	3.41E+00	4.48E+00	5.19E+00	≤2.50E+01
	2.	Average release rate for period	μCi/sec	5.07E-01	4.34E-01	5.64E-01	6.52E-01	
	3.	Applicable ODCM Limit	μονs ο ς %	3.07 L-01 *	*	3.04L-01 *	*	
*E.		RCENT OF APPLICABLE OCM LIMITS						
	FIS	SSION AND ACTIVATION GASES						
	1.	Quarterly gamma air dose limit	%	5.37E-02	9.25E-02	1.24E-01	2.34E-02	
	2.	Quarterly beta air dose limit	%	2.12E-01	1.10E-01	7.34E-02	8.54E-03	
	3. 4.	Yearly gamma air dose limit Yearly beta air dose limit	% %	2.68E-02 1.06E-01	4.62E-02 5.48E-02	6.18E-02 3.67E-02	1.17E-02 4.27E-03	
	4. 5.	Whole body dose rate limit	% %	3.60E-02	5.50E-02	1.29E-02		
	6.	Skin dose rate limit	%	1.03E-02	1.53E-02	4.70E-03	3.46E-03	
		LOGENS, TRITIUM AND PARTIC TH HALF-LIVES >8 DAYS	CULATES					
	7.	Quarterly dose limit (organ)	%	9.01E-02	9.28E-02	6.37E-02	3.72E-01	
	8.	Yearly dose limit (organ)	%	4.51E-02	4.64E-02	3.18E-02	1.86E-01	
	9.	Organ dose rate limit	%	5.00E-05	3.87E-05	2.01E-05	6.18E-04	

TABLE 1B
GASEOUS EFFLUENTS--ELEVATED RELEASE

NUCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	CONTINUO QUARTER 2	US MODE QUARTER 3	QUARTER 4
1. Fission Gases					
Argon-41	Ci	2.32E+00	1.99E+00	1.83E+00	1.45E+00
Krypton-85	Ci				1.35E+01
Krypton-85m	Ci	4.60E+01	4.76E+01	7.67E+01	1.69E+01
Krypton-87	Ci	1.15E+00	3.40E+00	6.76E+00	8.61E-01
Krypton-88	Ci	2.57E+01	3.61E+01	9.02E+01	1.66E+01
Krypton-89	Ci		5.53E+00	0.045.04	4.405.04
Xenon-133	Ci	5.71E+01	5.36E+01	8.21E+01	1.43E+01
Xenon-135	Ci	1.40E+00	2.64E+00	1.15E+00	7.40E-01
Xenon-135m	Ci	6.28E+00	1.21E+01	3.48E+00	9.63E-01
Xenon-137	Ci	3.12E+01	6.77E+01	1.33E+01	1.02E+00
Xenon-138	Ci	1.80E+01	3.82E+01	1.06E+01	1.68E+00
TOTAL	Ci	1.88E+02	2.69E+02	2.86E+02	6.80E+01
2. <u>Iodines</u>					
lodine-131	Ci	3.07E-04	2.56E-04	1.69E-04	5.05E-04
lodine-133	Ci	1.56E-03	4.09E-04	2.28E-04	6.96E-05
lodine-135	Ci	1.35E-03	3.93Ę-05	8.31E-05	
TOTAL	Ci	3.22E-03	7.04E-04	4.80E-04	5.75E-04
3. Particulates					
Chromium-51	Ci				1.56E-06
Manganese-54	Ci		***********		8.83E-07
Cobalt-60	Ci			***********	4.34E-07
Strontium-89	Çi	4.64E-05	1.26E-04	1.51E-04	1.13E-04
Strontium-90	Ci	3.58E-07	2.20E-07	3.61E-07	5.74E-07
Cesium-137	Ci		6.35E-07	2.33E-07	2.18E-07
Barium-140	Ci	6.32E-05	7.31E-05	2.97E-05	4.59E-05
TOTAL	Ci	1.10E-04	2.00E-04	1.81E-04	1.63E-04
4. Tritium					
Hydrogen-3	Ci	4.37E-01	4.48E-01	8.46E-01	1.23E+00

Note: There were no batch releases for this report period.

TABLE 1C GASEOUS EFFLUENTS--GROUND LEVEL RELEASES

NUCLIDES RELEASED	UNIT	QUARTER 1	CONTINUO QUARTER 2	US MODE QUARTER 3	QUARTER 4
NUCLIDES RELEASED	UNII	<u>OUARTER I</u>	OUAKTER 2	OUAKTER 5	QUARTER 4
1. Fission Gases					
Krypton-87 Xenon-133 Xenon-135 Xenon-135M Xenon-137 Xenon-138	Ci Ci Ci Ci Ci	6.76E-02 7.43E-01 3.86E+00 1.83E+01 1.32E+02 7.01E+01 2.25E+02	1.54E+00 4.44E+00 1.70E+01 5.10E+01 5.94E+01 1.33E+02	1.40E+00 3.19E+00 1.32E+01 3.02E+01 5.25E+01 1.00E+02	7.28E+00 1.01E+00 1.10E+00 3.16E+00 3.80E+00
2. <u>Iodines</u>					٠.
lodine-131 lodine-133	Ci Ci	2.73E-04 6.91E-04	3.28E-04 6.98E-04	2.28E-04 6.07E-04	1.71E-03 3.54E-04
TOTAL	Ci	9.64E-04	1.03E-03	8.35E-04	2.06E-03
3. Particulates					
Manganese-54 Cobalt-60 Zinc-65 Strontium-89 Strontium-90 Barium-140 TOTAL	Ci Ci Ci Ci Ci	1.68E-04 3.95E-08 2.05E-04 3.73E-04	1.49E-06 	2.38E-04 1.36E-06 1.72E-04 4.11E-04	6.23E-06 1.92E-06 7.66E-06 9.65E-05 2.08E-06 7.14E-06
4. <u>Tritium</u>	O :		0.005.00	0.045.00	0.005.00
Hydrogen-3	Ci	3.55E+00	2.96E+00	3.64E+00	3.90E+00

Note: There were no batch releases for this report period.

TABLE 1D - SUPPLEMENTAL GASEOUS EFFLUENTS—UNMONITORED SHORT-TERM RELEASE

			<u>CONTINUO</u>	<u>US MODE</u>	
NUCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
1. Fission Gases					
None					
2. <u>Iodines</u>					
None		•			
3. Particulates					
Chromium-51	Ci	********			1.57E-08
Manganese-54	Ci				1.53E-07
Cobalt-58	Ci				5.40E-08
Iron-59	Ci				9.67E-09
Cobalt-60	Ci				1.55E-07
Zinc-65	Ci	******			2.09E-06
TOTAL	Ci				2.48E-06
4. <u>Tritium</u>					
Hydrogen-3	Ci				6.24E-02

TABLE 2A LIQUID EFFLUENTS--SUMMATION OF ALL RELEASES

			<u>UNIT</u>	OTR 1	OTR 2	OTR 3	OTR 4	EST TOTAL ERROR %
A.	FIS	SSION AND ACTIVATION PRODU	UCTS			,		
	1. 2.	Total Release (not including tritium, gases and alpha) Average diluted concentration	Ci	NONE	NONE	NONE	3.67E-04	≤2.50E+01
	3.	during period Applicable ODCM Limit	μCi/ml %	NONE	NONE	NONE 	1.33E-10 *	
В.	TR	ITIUM						
*	1. 2.	Total Release Average diluted concentration	Ci	7.82E-06	1.80E-04	5.46E-04	3.81E+00	≤2.50E+01
	3.	during period (Note 1) Applicable ODCM Limit	μCi/ml %	1.17E-06 *	2.31E-06 *	2.11E-06 *	1.47E-06 *	
C.	DIS	SSOLVED AND ENTRAINED GAS	ES					
	1. 2.	Total Release Average diluted concentration	Ci	NONE	NONE	NONE		≤2.50E+01
	3.	during period Applicable ODCM Limit	μCi/ml %	NONE	NONE	NONE 		
D.	CD	OSS ALPHA RADIOACTIVITY			•			
υ.	1.	Total Release	Ci	NONE	NONE	NONE	5.17E-06	≤4.20E+01
	••	Total Florodoo	0.		110112	110112	02 00	
E.		LUME OF WASTE RELEASED RIOR TO DILUTION)	liters	3.30E+03	1.91E+04	1.51E+05	9.34E+05	
F.		LUME OF DILUTION WATER ED DURING PERIOD	liters	1.51E+08	2.47E+08	2.32E+08	2.57E+09	
*G		RCENT OF APPLICABLE OCM LIMITS						
	1. 2. 3. 4.	Quarterly Whole Body Dose Quarterly Organ Dose Annual Whole Body Dose Annual Organ Dose	% % %	8.58E-05 2.57E-05 4.29E-05 1.29E-05	3.19E-04 9.57E-05 1.59E-04 4.78E-05	1.87E-04 5.61E-05 9.34E-05 2.80E-05	8.50E-04 2.63E-04 4.25E-04 1.32E-04	

(Note 1) Concentration includes summation from diluted and undiluted values from Canal and Non-Canal releases (Table 2B).

TABLE 2B LIQUID EFFLUENTS CANAL

			BATO	CH MODE	
NUCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
1. Fission and Activation Products	i				
Manganese-54	Ci		••••		1.04E-04
Iron-55	Ci				2.02E-04
Cobalt-60	Ci				1.59E-05
Zinc-65	Ci		**********		3.83E-05
Strontium-90	Ci		•••••		7.06E-06
TOTAL	Ci			·	3.67E-04
2. <u>Tritium</u>					
HYDROGEN-3	Ci	7.81E-06	1.80E-04	5.47E-04	3.81E+00
3. <u>Dissolved and Entrained Gases</u>		·			
NONE	Ci	***************************************			

Note: There were no continuous mode discharges during this report period.

TABLE 2B (SUPPLEMENT) LIQUID EFFLUENTS NON-CANAL

•			BATO	CH MODE	
NUCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
1. Fission and Activation Produ	icts				
NONE	Ci		***********		
2. <u>Tritium</u>	ì				
HYDROGEN-3	Ci	3.87E-06	2.64E-05	3.19E-04	8.79E-05
3. Dissolved and Entrained Gas	<u>es</u>				
NONE	Ci				

Note: There were no continuous mode discharges during this report period.

TABLE 3A SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

A. SOLID WASTE SHIPPED OFFSITE FOR BURIAL OR DISPOSAL (NOT IRRADIATED FUEL)

		•	•			Est. i otai
1.	Type of Waste	Unit	Class A	Class B	Class C	Error %
	a. Spent resins, filter sludges	m^3	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	evaporator bottoms, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	b. Dry compressible waste,	m^3	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	contaminated equipment, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	c. Irradiated components,	m^3	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	control rods, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	d. Other: Dry compressible	m^3	1.08E+03	5.83E+00	0.00E+00	1.00E+01
	waste, contaminated equipment, spent resins for volume reduction.	Ci	2.76E+01	5.13E+01	0.00E+00	1.00E+01

- 2. Estimate of Major Nuclide Composition (by type of waste)
 - a. Spent resins, filter sludges, evaporator bottoms, etc.

NONE

b. Dry compressible waste, contaminated equipment, etc.

NONE

c. Irradiated components, control rods, etc.

NONE

d. Other: Dry compressible waste, contaminated equipment, spent resins for volume reduction.

Isotope	Percent	Curies		Isotope	Percent	Curies	
Iron-55	6.94E+01	5.47E+01	Ε	Nickel-63	9.24E-01	7.29E-01	Ε
Cobalt-60	1.09E+01	8.59E+00	E	'Tritium	5.39E-01	4.25E-01	Ε
Manganese-54	2.67E+00	2.11E+00	Ε	Cesium-134	1.49E+00	1.17E+00	Ε
Cesium-137	2.78E+00	2.19E+00	Ε	Cobalt-58	1.60E-02	1.26E-02	Ε
Zinc-65	1.06E+01	8.38E+00	Ε	Cerium-141	1.47E-02	1.16E-02	Ε
Plutonium-241	2.44E-02	1.93E-02	E	Strontium-90	3.13E-01	2.47E-01	Ε
Cerium-144	3.15E-01	2.48E-01	Е				

(E- Estimated M- Measured)

Percentage of nuclides and total activities are based on a combination of direct measurements and scaling for non-gamma emitting nuclides.

TABLE 3A (continued) SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

3. Solid Waste Disposition

No. of Shipments	Mode of Transportation	<u>Destination</u>
14	Truck	*Duratek Oak Ridge, TN
7	Truck	* Studsvik Erwin, TN
10	Truck	* Alaron Wampum, PA
7	Truck	*Duratek GIC Kingston, TN
2	Truck	*GE Global Nuclear Fuel Wilmington, NC
* Volume Deduc	tion Facility	

^{*-} Volume Reduction Facility

B. IRRADIATED FUEL SHIPMENTS (Disposition)

No. of Shipments	Mode of Transportation	<u>Destination</u>
NONE		

TABLE 3B SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

NRC CLASS A

SOURCE OF WASTE	PROCESSING EMPLOYED	CONTAINER <u>VOLUME</u>	TYPE OF CONTAINER	NUMBER OF CONTAINERS
Spent Resins, Filter Sludges, evaporator Bottoms, etc.	Air Drying Non-compacted	205.8 ft^3	HIC	4
Dry compressible Waste (DAW), Contaminated Equipment, etc.	Non-compacted	1280 ft^3	STC	13
Dry compressible Waste(DAW), Contaminated Equipment, etc.	Non-compacted	2560 ft^3	STC	1
Dry compressible Waste(DAW), Contaminated Eqiupment, etc.	Non-compacted	96 ft^3	STC	47
Contaminated Oil	Non-compacted	7.5 ft^3	STC	13
Dry compressible Waste(DAW), Contaminated Equipment	Non-compacted	111 ft^3	STC	3
Dry compressible Waste(DAW), Contaminated Equipment	Non-compacted	206.1 ft^3	STC	1
Dry compressible Waste(DAW), Contaminated Equipment	Non-compacted	209.1 ft^3	STC	1
Dry compressible Waste(DAW), Contaminated Equipment	Non-compacted	292 ft^3	STC	5
Dry compressible Waste(DAW), Contaminated Equipment	Non-compacted	1033.5 ft^3	STC	
		15		

В.	NRC	CL	ASS	В
----	-----	----	-----	---

SOURCE OF WASTE	PROCESSING EMPLOYED	CONTAINER VOLUME	TYPE OF CONTAINER	NUMBER OF CONTAINERS
Spent Resins, Filter Sludges, evaporator Bottoms, etc.	Air Drying Non-compacted	205.8 ft^3	HIC	1
C. NRC CLASS C				
SOURCE OF WASTE	PROCESSING EMPLOYED	CONTAINER VOLUME	TYPE OF CONTAINER	NUMBER OF CONTAINERS
NONE			•••••	

Solidification Agent:

NONE

HIC- High Integrity Container STC-Strong Tight Container

ATTACHMENT NO. 1

CHANGES TO THE OFFSITE DOSE CALCULATION MANUAL (ODCM)

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 6.2.3, changes made to the Offsite Dose Calculation Manual (ODCM) during the reporting period shall be included in the Annual Radioactive Effluent Release Report.

There were no changes to the Offsite Dose Calculation Manual (ODCM).

ATTACHMENT NO. 2

SUMMARY OF CHANGES TO THE PROCESS CONTROL PROGRAM

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 6.2.3, changes made to the Process Control Program (PCP) during the reporting period shall be included in the Annual Radioactive Effluent Release Report.

Revisions to the Performance Reference procedures of the Process Control Program procedure were made and approved on 5/22/06. These revisions do not reduce the overall conformance of the solidified waste product to existing criteria for solid waste. Listed below is a brief summary of changes incorporated in this revision.

- 1) CNSI-FO-OP-032-41802, Setup and Operating Procedure for RDS-1000 Unit Number 9 at James A. FitzPatrick Nuclear Power Plant was withdrawn and replaced by CNSI-FO-P-033-41802. This was due to an equipment change to replace obsolete and unreliable equipment.
- 2) CNSI-FO-OP-023-41802, Bead Resin/Activated Carbon Dewatering Procedure for CNSI-14-215 or Smaller liners at James A. FitzPatrick Nuclear Plant was revised to dewater liners with new equipment. The major change was the new procedure uses multiple drying cycles instead of an air conditioning system to dewater liners.

ATTACHMENT NO. 3

SUMMARY OF CHANGES TO THE ENVIRONMENTAL MONITORING AND DOSE CALCULATION LOCATIONS

In accordance with the James A. FitzPatrick Nuclear Power Plant Off Site Dose Calculation Manual (ODCM), Part 1, Sections 6.2.3 a listing of new locations for dose calculation and/or environmental monitoring identified by the land use census shall be included in the Annual Radioactive Effluent Release Report.

CHANGES IN ENVIRONMENTAL MONITORING LOCATIONS

During the report period, no changes were made to the Environmental Monitoring Locations sampled to implement the requirements of the ODCM, Part 1, table 5.1-1. Sample location selections were based on the 2006 annual land use census.

NEW LOCATIONS FOR DOSE CALCULATIONS

During the report period, no changes in Dose Calculation Receptor Locations were required based on the results of the land use census.

ATTACHMENT NO. 4

DEVIATIONS FROM THE REQUIRED ENVIRONMENTAL SAMPLING SCHEDULE

In accordance with the James A. FitzPatrick Nuclear Power Plant Off Site Dose Calculation Manual (ODCM), Part 1, Section 6.2.7 the cause for the unavailability of any environmental samples required during the report period shall be included in the Annual Radioactive Effluent Release Report.

The following reports samples that were a deviation from the requirements of ODCM Part 1, Table 5.1-1. ODCM Part I, Section 5.1.1.c.1 allows for deviations from the program due to hazardous conditions, seasonal unavailability, theft, uncooperative residents, or to malfunction of automatic sampling equipment.

DEVIATION AND EXCEPTIONS TO THE PROGRAM

The noted exceptions to the 2006 sample program address only those samples or monitoring requirements which are required by the ODCM, Part I, Table 5.1-1. This section satisfies the reporting requirements of ODCM, Part I, Section 5.1.1.c.1.

A. ODCM Program Deviations

The following are deviations from the program specified by the ODCM:

- 1. The air sampling pump at the R5 Environmental Sampling Station was inoperable for approximately 3 hours during the sample period of 1/17/06 through 1/24/06. The air sample pump was running at the time of sample collection. The sample pump out of service time was determined based on the sample pump run time integrator. The inoperability of the pump was due to a loss of power to the sampler. No corrective actions were required to restore the unit to service.
- 2. The air sampling pump at the R3 and R4 Environmental Sampling Stations were inoperable for approximately 1 hour on 2/22/06 due to high winds that caused a power outage. The sample pump out of service times were determined based on the sample pump run time integrator. No corrective actions were implemented.
- 3. The air sampling pump at the R5 Environmental Sampling Station was inoperable for approximately 2.6 hours on 2/22/06 due to high winds that caused a power outage. The sample pump out of service time was determined based on the sample pump run time integrator. No corrective action was implemented.

ATTACHMENT NO. 4 (Continued)

- 4. The air sampling pump at the R1 and R2 Environmental Sampling Stations were inoperable for approximately 0.8 hours during the sample period of 3/28/06 through 4/4/06. The air sample pumps were running at the time of sample collection. The sample pump out of service times were determined based on the sample pump run time integrators. The inoperability of the pumps was due to a loss of power to the samplers. No corrective actions were required to restore these units to service.
- 5. The air sampling pump at the R5 Environmental Sampling Station was inoperable for approximately 2.4 hours on 6/6/06. The sample pump out of service time was determined based on the sample pump run time integrator. The inoperability of the pump was due to a loss of power to the sampler. No corrective actions were required to restore the unit to service.
- 6. The air sampling pump at the R1 and R2 Environmental Sampling Stations were inoperable for approximately 0.7 hours on 8/1/06. The sample pump out of service times were determined based on the sample pump run time integrators. The inoperability of the pumps was due to a loss of power to the samplers. No corrective actions were required to restore the unit to service.
- 7. The air sampling pump at the R5 Environmental Sampling Stations was inoperable for approximately 2.5 hours during the sample period of 9/26/06 through 10/3/06. The air sample pump was running at the time of sample collection. The sample pump out of service time was determined based on the sample pump run time integrator. The inoperability of the pump was due to a loss of power to the sampler. No corrective actions were required to restore these units to service.
- 8. The air sampling pump at R1 and R2 Environmental Sampling Stations were inoperable for approximately 9.7 hours for the sample period 10/23/06 through 10/31/06. The sample pump out of service times were determined based on the sample pump run time integrators. The sample pumps were found running. The inoperability of the pumps was due to a loss of power caused by strong winds. No corrective actions were required to restore the unit to service.
- 9. The air sampling pump at the R5 Environmental Sampling Stations was inoperable for approximately 2.0 hours during the sample period of 12/05/06 through 12/12/06. The air sample pump was running at the time of sample collection. The sample pump out of service time was determined based on the sample pump run time integrator. The inoperability of the pump was due to a loss of power to the sampler. No corrective actions were required to restore these units to service.

ATTACHMENT NO. 4 (Continued)

B. Air Sampling Station Operability Assessment

The ODCM required air sampling program consists of 5 individual sampling locations. The collective operable time period for the air monitoring stations was 43,763 hours out of a possible 43,800 hours. The air sampling availability factor for the report period was 99.92%.

ATTACHMENT NO. 5

ANNUAL SUMMARY OF HOURLY METEOROLOGICAL DATA

The James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1, Radiological Controls (REC) Section 6.2 and 6.2.2 states in part: The Annual Radioactive Effluent Release Report submitted prior to May 1 of each year may include an annual summary of meteorological data collected over the previous year. If the meteorological data is not included, the licensee shall retain it on file and provide it to the U.S. Nuclear Regulatory Commission upon request. In accordance with the aforementioned ODCM requirement, meteorological data is not included in this report. It is retained on file and is available upon request.

ATTACHMENT NO. 6

MAJOR MODIFICATIONS TO RADIOACTIVE LIQUID, GASEOUS AND SOLID WASTE TREATMENT SYSTEMS

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 7.0, Major Modifications to Radioactive Waste Treatment Systems (liquid, gaseous and solid) shall be reported in the Annual Radioactive Effluent Release Report for the period in which the modification is completed and made operational.

There were no major modifications to any liquid, gaseous, or solid radioactive waste treatment systems.

ATTACHMENT NO. 7

GASEOUS EFFLUENTS – UNMONTIORED SHORT-TERM RELEASE

a) **Date:** October 28, 2006

b) Location: Unmonitored Release from the Reactor Building via the

Decay Heat Removal System Basin

c) **Duration:** 16 Hours and 32 minutes

d) Flowrate: 2.80E+05 cfm

e) Volume Released: 2.78E+08

f) Nuclides Released: See Table 1 – Supplemental

Gaseous Effluents - Unmonitored Short-Term Release

g) Resultant Doses: See Addendum 1—Assessment of Radiation Doses to the Public

January-December 2006 Table 1.D

h) Dose Calculations: Doses were calculated in accordance with the Offsite Dose

Calculation Manual (ODCM) Section 4.4.3 Short Term Releases

ADDENDUM 1

ASSESSMENT OF RADIATION DOSES TO THE PUBLIC JANUARY - DECEMBER 2006

1. INTRODUCTION

The James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls, requires an assessment of the radiation doses to the public due to radioactive liquid and gaseous effluents. This assessment of doses to the public is based on accepted methodologies found in the Offsite Dose Calculation Manual (ODCM).

2. DOSE LIMITS

A. DOSE FROM LIQUID EFFLUENTS (ODCM, Part 1, REC 2.3)

Applicability

Applies to doses from radioactive material in liquid effluents.

Objective

To ensure that the dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The dose to a member of the public from radioactive materials released from the plant in liquid effluents to unrestricted areas shall be limited as follows:

- 1. During any calendar quarter, limited to less than or equal to 1.5 mrem to the whole body and to less than or equal to 5 mrem to any organ.
- 2. During any calendar year, limited to less than or equal to 3 mrem to the whole body and to less than or equal to 10 mrem to any organ.

B. GASEOUS DOSE RATES (ODCM, Part 1, REC 3.2)

Applicability

Applies to the radiation dose from radioactive material in gaseous effluents.

ADDENDUM 1 (continued)

Objective

To ensure that the dose rates at or beyond the site boundary from gaseous effluents do not exceed the annual dose limits of 10 CFR 20, for unrestricted areas.

Specifications

The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluents shall be limited as follows:

- 1. Less than or equal to 500 mrem/year to the whole body and less than or equal to 3000 mrem/year to the skin from noble gases; and,
- 2. Less than or equal to 1500 mrem/year to any organ from Iodine-131, Iodine-133, Tritium and for radioactive materials in particulate form with half-lives greater than 8 days (inhalation pathway only).

C. AIR DOSE, NOBLE GASES (ODCM, Part 1, REC 3.3)

Applicability

Applies to the air dose due to noble gases in gaseous effluents.

Objective

To ensure that the noble gas dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The air dose to areas at or beyond the site boundary from noble gases released from the plant in gaseous effluents shall be limited:

- 1. During any calendar quarter, to less than or equal to 5 mrad from gamma radiation, and less than or equal to 10 mrad from beta radiation; and,
- 2. During any calendar year, to less than or equal to 10 mrad from gamma radiation and less than or equal to 20 mrad from beta radiation.

ADDENDUM 1 (continued)

D. <u>DOSE DUE TO IODINE-131, IODINE-133, TRITIUM AND</u>
<u>RADIONUCLIDES IN PARTICULATE FORM</u> (ODCM, Part 1, REC 3.4)

Applicability

Applies to the cumulative dose from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days in gaseous effluents.

<u>Objective</u>

To ensure that the dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The dose to a member of the public at or beyond the site boundary from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days released from the plant in gaseous effluents shall be limited:

- 1. During any calendar quarter to less than or equal to 7.5 mrem to any organ; and,
- 2. During any calendar year to less than or equal to 15 mrem to any organ.

E. TOTAL DOSE FROM URANIUM FUEL CYCLE (ODCM, Part 1, REC 4.0)

Applicability

Applies to radiation dose from releases of radioactivity and radiation from uranium fuel cycle sources.

Objective

To ensure that the requirements of 40 CFR 190 are met.

ADDENDUM 1 (continued)

Specifications

The dose or dose commitment to any member of the public, due to releases of radioactivity and radiation, from uranium fuel cycle sources shall be limited as follows:

- 1. Less than or equal to 25 mrem/year to the whole body; and,
- 2. Less than or equal to 25 mrem/year to any organ except the thyroid which shall be limited to less than or equal to 75 mrem/year.

3. DOSE ASSESSMENT

A. <u>METHODOLOGY</u>

The assessment of radiation doses to the public due to radioactive liquid and gaseous effluents is performed in accordance with the ODCM. The ODCM is based on methodologies and models suggested by the "Guidance Manual For Preparation of Radiological Effluent Technical Specifications for Nuclear Power Plants" (NUREG-0133) and "Calculation of Annual Doses to Man from Routine Releases of Reactor Effluents for the purpose of Evaluating Compliance with 10CFR50, Appendix I" (Regulatory Guide 1.109).

B. ASSUMPTIONS

Dose calculations are performed using formulas and constants defined in the ODCM. Specific radioactive release activities used in the dose calculations are listed in the Annual Radioactive Effluent Release Report (1.21 Report) for the period of January 1, 2006 to December 31, 2006. Historical meteorological data was used to generate tables of average dispersion factors. Locations of interest were identified from the 2006 land use census. Dispersion factors and locations of interest used in performing the dose calculations are listed in Table 2.

C. ASSESSMENT RESULTS SUMMARY

The calculated doses to the public due to radioactive effluents are listed in Table 1. The calculated doses are small fractions of their respective dose limits.

ADDENDUM 1 (continued)

4. 40 CFR 190 DOSE ASSESSMENT

A. METHODOLOGY

Evaluation to demonstrate compliance with the 40 CFR 190 dose limits must be performed when the doses calculated for 10 CFR 50 compliance exceed twice their respective limits. When additional dose assessment is required to demonstrate compliance with 40 CFR 190 it is performed in accordance with the ODCM.

B. RESULTS SUMMARY

The cumulative dose contribution from liquid and gaseous effluents for this report period were calculated and are listed in Table 1. The cumulative dose contribution from direct radiation from the reactor unit and from radwaste storage tanks is measured by environmental thermoluminescent dosimeters for the report period. This data is contained in the Annual Environmental Operating Report. The calculated doses from liquid and gaseous effluents are less than twice their respective 10 CFR 50 limits, therefore, additional calculations are not necessary to demonstrate compliance with 40 CFR 190 dose limits (ODCM, Part 1, REC 4.1.1.c)

ADDENDUM 1 (continued)

TABLE 1 ANNUAL DOSE ASSESSMENT 2006

		A. LIQU	IDS		
QUARTER	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	ANNUAL
	(a)	(a)	(a)	(a)	(a)
Organ (mrem) % of Limit	1.29E-06 2.57E-05	4.78E-06 9.57E-05	2.80E-06 5.61E-05	1.32E-05 2.63E-04	2.21E-05 2.21E-04
	(b)	(b)	(b)	(b)	(b)
Whole Body (mrem) % of Limit	1.29E-06 8.58E-05	4.78E-06 3.19E-04	2.80E-06 1.87E-04	1.32E-05 8.50E-04	2.21E-05 7.37E-04

- (a) Dose to the Child Liver primarily by the potable water pathway.
- (b) Dose to the Child Whole Body primarily by the potable water pathway.

B. NOBLE GASES						
<u>QUARTER</u>	1	<u>2</u>	<u>3</u>	<u>4</u>	ANNUAL	
Total Body (mrem/yr) % of Limit	1.80E-01	2.75E-01	6.43E-02	6.20E-02	2.75E-01	
	3.60E-02	5.50E-02	1.29E-02	1.24E-02	5.50E-02	
Skin (mrem/yr) % of Limit	3.09E-01	4.60E-01	1.41E-01	1.04E-01	4.60E-01	
	1.03E-02	1.53E-02	4.70E-03	3.46E-03	1.53E-02	
Gamma (mrad)	2.68E-03	4.62E-03	6.18E-03	1.17E-03	1.47E-02	
% of Limit	5.37E-02	9.25E-02	1.24E-01	2.34E-02	1.47E-01	
Beta (mrad) % of Limit	2.12E-02	1.10E-02	7.34E-03	8.54E-04	4.03E-02	
	2.12E-01	1.10E-02	7.34E-02	8.54E-03	2.02E-01	

ADDENDUM 1 (continued)

TABLE 1 ANNUAL DOSE ASSESSMENT 2006

C. IODINES AND PARTICULATES							
<u>QUARTER</u>	<u>1</u>	· <u>2</u>	<u>3</u>	<u>4</u>	ANNUAL		
	(a)	(b)	(a)	(b)	(b)		
Organ (mrem)	6.76E-03	6.96E-03	4.78E-03	2.79E-02	4.64E-02		
% of Limit	9.01E-02	9.28E-02	6.37E-02	3.72E-01	3.09E-01		
	(c)	(c)	(c)	(c)	(c)		
Organ Dose Rate (mrem/yr)	7.51E-04	5.81E-04	3.01E-04	9.26E-03	9.26E-03		
% of Limit	5.00E-05	3.87E-05	2.01E-05	6.17E-04	6.17E-04		

- (a) Dose to the Infant Thyroid primarily by the goats milk pathway.
- (b) Dose to the Infant Thyroid primarily by the cows milk pathway.
- (c) Dose to the Child Thyroid primarily by the vegetation pathway.

D. UNMONITORED SHORT-TERM RELEASE QUARTER 4

QUARTER	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u> ·	<u>ANNUAL</u>
				(a)	(b)
Organ (mrem) % of Limit				1.45E-04 1.93E-03	1.45E-04 9.67E-04
Organ Dose Rate	·			6.28E-04	6.28E-04
(mrem/yr) % of Limit				4.19E-05	4.19E-05

- (a) Dose to the Child Liver primarily by the vegetation pathway.
- (b) Dose to the Child Thyroid primarily by the vegetation pathway.

ADDENDUM 1 (continued)

TABLE 2 METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

	RECEPTOR	GEOGRAPHIC LOCATION		ATMOS DISPERSION	PHERIC** N FACTOR
Α.	IODINE & PARTICULATES	DISTANCE/ DIRECTION	RELEAS: POINT	E X/Q (sec/m ³)	D/Q (l/m²)
1.	Garden	0.90 mi @ 83°E	ST	2.83E-08*	1.75E-09
	Grazing Season	0.90 mi @ 83°E	RX	2.02E-07*	5.01E-09
	Cary	0.90 mi @ 83°E	TB	1.83E-07*	4.80E-09
	Location No. 78	0.90 mi @ 83°E	RF	2.02E-07*	5.01E-09
		0.90 mi @ 83°E	RW	3.21E-07*	5.76E-09
2.	Meat	1.18 mi @ 127°SE	ST	1.72E-08*	6.80E-10
	Grazing Season	1.18 mi @ 127°SE	RX	5.36E-08*	1.30E-09
	Parkhurst	1.18 mi @ 127°SE	TB	5.14E-08*	1.27E-09
	Location No. 26	1.18 mi @ 127°SE	RF	5.36E-08*	1.30E-09
		1.18 mi @ 127°SE	RW	9.12E-08*	1.46E-09
3.	Cow	2.50 mi @ 139°SE	ST	1.67E-08*	2.65E-10
	Grazing Season	2.50 mi @ 139°SE	RX	2.76E-08*	4.14E-10
	France	2.50 mi @ 139°SE	TB	2.71E-08*	4.07E-10
	Location No. 10	2.50 mi @ 139°SE	RF	2.76E-08*	4.14E-10
		2.50 mi @ 139°SE	RW	4.15E-08*	4.36E-10
4.	Goat (D/Q)	3.62 mi @ 113°ESE	ST		2.28E-10
	Grazing Season	3.62 mi @ 113°ESE	RX		3.40E-10
	Showers	3.62 mi @ 113°ESE	TB		3.33E-10
	Location No. 71	3.62 mi @ 113°ESE	RF		3.40E-10
		3.62 mi @ 113°ESE	RW		3.49E-10
5.	Goat (X/Q)	2.64 mi @ 152°SSE	ST	1.94E-08*	
	Grazing Season	2.64 mi @ 152°SSE	RX	2.58E-08*	
	Nickolas	2.64 mi @ 152°SSE	TB	2.57E-08*	
	Location No. 61	2.64 mi @ 152°SSE	RF	2.58E-08*	
		2.64 mi @ 152°SSE	RW	3.59E-08*	

ADDENDUM 1 (continued)

TABLE 2 METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

RECEPTOR	GEOGRAPHIC LOCATION		ATMOSPHERIC** DISPERSION FACTOR		
A. IODINE & PARTICULATES	DISTANCE/ DIRECTION	RELEASI POINT	E X/Q (sec/m3)	D/Q (l/m2)	
6. Resident Annual Average					
 a. Inhalation⁽²⁾ Cary Location No. 78 	1.55 mi @ 90°E ⁽¹⁾ 0.90 mi @ 83°E 0.90 mi @ 83°E 0.90 mi @ 83°E 0.90 mi @ 83°E	ST RX TB RF RW	2.99E-08 2.07E-07 1.88E-07 2.07E-07 3.06E-07		
b. Deposition ⁽³⁾ Whaley Location No. 199	0.71 mi @ 118°ESE 0.71 mi @ 118°ESE 0.71 mi @ 118°ESE 0.71 mi @ 118°ESE 0.71 mi @ 118°ESE	ST RX TB RF RW		1.60E-09 5.52E-09 5.30E-09 5.52E-09 6.28E-09	
B. NOBLE GASES 1. Air Dose Annual Average Site Boundary	1.55 mi @ 90°E ⁽¹⁾ 0.60 mi @ 90°E	ST ST(fc) RX TB RF RW	2.99E-08 1.16E-07 3.58E-07 3.19E-07 3.58E-07 5.39E-07		
2. Total Body Annual Average Site Boundary	0.60 mi @ 90°E 0.60 mi @ 90°E 0.60 mi @ 90°E 0.60 mi @ 90°E 0.60 mi @ 90°E	ST(fc) RX TB RF RW	1.16E-07 3.58E-07 3.19E-07 3.58E-07 5.39E-07		

ADDENDUM 1 (continued)

TABLE 2 METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

RECEPTOR	GEOGRAPHIC LOCATION	ATMOSPHERIC** DISPERSION FACTOR		
B. NOBLE GASES (continued)	DISTANCE/ DIRECTION	RELEASE POINT	X/Q (sec/m3)	D/Q (l/m2)
3. Skin	1.55 mi @ 90°E	ST	2.99E-08	
Annual Average	0.60 mi @ 90°E	ST(fc)	1.16E-07	
Site Boundary	0.60 mi @ 90°E	RX	3.58E-07	
	0.60 mi @ 90°E	TB	3.19E-07	
	0.60 mi @ 90°E	RF	3.58E-07	
	0.60 mi @ 90°E	RW	5.39E-07	

^{*} Tritium Dose Calculation

- (1) Highest Sector Average X/Q in a populated area, not an identified residence.
- (2) Inhalation uses Annual Average X/Q values. All other receptors use grazing season meteorology.
- (3) Deposition uses Annual Average D/Q values. All other receptors use grazing season meteorology.

ST = Main Stack

RX = Reactor Building Vent

TB = Turbine Building Vent

RF = Refuel Floor Vent

RW = Radwaste Building Vent

fc = Finite Cloud

^{**} Based on ODCM X/Q, D/Q Values Rev. 08