

April 30, 2008 JAFP-08-0037 Entergy Nuclear Northeast Entergy Nuclear Operations, Inc. James A. Fitzpatrick NPP P.O. Box 110 Lycoming, NY 13093 Tel 315 342 3840

the stage taken the st

والأرابي وأقريه الإرتجار الكرائي والمحافي

11,19,19,11

and the spectrum

U.S. Nuclear Regulatory Commission ATTN: Document Control Desk Washington, D.C. 20555-0001

SUBJECT: Entergy Nuclear Operations, Inc. James A. FitzPatrick Nuclear Power Plant Docket No. 50-333 License No. DPR-59

Annual Radiological Effluent Release Report

Dear Sir or Madam:

Attached is the <u>Annual Radioactive Effluent Release Report</u> for the period of January 1, 2007 through December 31, 2007. This report is submitted in accordance with the requirements of the James A. FitzPatřick Nuclear Power Plant Offsite Dose Calculation Manual, Part 1, Radiological Controls, Section 6.2.

This report includes, as an Addendum, an Assessment of the Radiation Doses to the public due to the radioactive liquid and gaseous effluents released during the 2007 calendar year. The format used for the effluent data is outlined in Appendix B of Regulatory Guide 1.21, Revision 1. Distribution is in accordance with Regulatory Guide 10.1, Revision 4.

If you have any questions concerning the attached report, please contact Crystal A. Boucher, Chemistry Superintendent, at the James A. FitzPatrick Nuclear Power Plant at (315)349-6748.

Very truly yours,

JAMES COSTEDIO LICENSING MANAGER - JAF

JC/CAB/jbh

Attachment: Annual Radiological Effluent Release Rerport

Xc: N

NRCResident InspectorS. Collins(USNRC Region 1)D. Sherman(ANI Library)K. Mulligan(JAF)C. Faison(ENOC/WPO)W. Hamblin (CHEM/JAF)

A. Muniz (USNRC Project Manager)P. Merges (NYSDEC)T. Kurtz (NMPC)J. Furfaro (ENV/JAF)J. McCann(ENOC/WPO)

ENTERGY NUCLEAR OPERATIONS, INC.

JAMES A. FITZPATRICK NUCLEAR POWER PLANT

ANNUAL RADIOACTIVE EFFLUENT RELEASE REPORT

JANUARY 1, 2007 - DECEMBER 31, 2007

DOCKET NO.: 50-333

LICENSE NO.: DPR-59

SUPPLEMENTAL INFORMATION

FACILITY: JAFNPP LICENSEE: ENTERGY NUCLEAR OPERATIONS, INC.

1. Offsite Dose Calculation Manual Part 1 Radiological Controls

a. Fission and Activation Gases:

- (1) The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluent shall be limited as follows:
 - (a) Less than or equal to 500 mrem/year to the whole body and less than or equal to 3000 mrem/year to the skin from noble gases.
- (2) The air dose to areas at or beyond the site boundary from noble gases released from the plant in gaseous effluent shall be limited:
 - (a) During any calendar quarter, to less than or equal to 5 mrad from gamma radiation, and less than or equal to 10 mrad from beta radiation; and,
 - (b) During any calendar year, to less than or equal to 10 mrad from gamma radiation and less than or equal to 20 mrad from beta radiation.
- b. Tritium, Iodines and Particulates, Half Lives > 8 days:
 - (1) The dose to a member of the public at or beyond the site boundary from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days released from the plant in gaseous effluent shall be limited:
 - (a) During any calendar quarter to less than or equal to 7.5 mrem to any organ; and,
 - (b) During any calendar year to less than or equal to 15 mrem to any organ.
 - (c) Less than 0.1% of the limits of Specification 3.4.1.c.1.a and 3.4.1.c.1.b as a result of burning contaminated oil.
 - (2) The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluents shall be limited as follows:
 - (a) Less than or equal to 1500 mrem/year to any organ from Iodine-131, Iodine-133, Tritium and for radioactive materials in particulate form with half-lives greater than 8 days (inhalation pathway only).

SUPPLEMENTAL INFORMATION (continued)

c. Liquid Effluents:

- The concentration of radioactive materials released to the unrestricted areas shall not exceed ten times the values specified in 10 CFR 20.1001-20.2402, Appendix B, Table 2, Column 2. For dissolved or entrained noble gases the concentration shall be limited to 2.00E-04 μCi/ml.
- (2) The dose to a member of the public from radioactive materials released from the plant in liquid effluents to unrestricted areas shall be limited as follows:
 - (a) During any calendar quarter, limited to less than or equal to 1.5 mrem to the whole body and to less than or equal to 5 mrem to any organ; and,
 - (b) During any calendar year, limited to less than or equal to 3 mrem to the whole body and to less than or equal to 10 mrem to any organ.

2. 10X Effluent Concentrations

					•	
a.	Fission and activation gases:	(No	ne specified)		na 2010 - Maria Angelan, Baka 2010 - Angelan Angelan, Baka	۰ ۰
b. [•]	Iodines:	(No	ne specified)			
c.	Particulates, half-lives >8 days:	(No	ne specified)	•		
d.	Liquid effluents:	Quarter 1	Quarter 2	Quarter 3	Quarter 4	
	(1) Fission and activation products (mixture EC) (μCi/ml)	None	None	None	9.35E-05	
	(2) Tritium (µCi/ml)	1.00E-02	1.00E-02	1.00E-02	1.00E-02	
	(3) Dissolved and entrained gases (μCi/ml)	2.00E-04	2.00E-04	2.00E-04	2.00E-04	

SUPPLEMENTAL INFORMATION (continued)

3. <u>Average Energy</u>

(None specified)

4. Measurements and Approximations of Total Radioactivity

- a. Fission and Activation Gases: Continuous monitor on each release path calibrated to a marinelli grab sample analyzed by gamma spectroscopy; bubbler grab sample analyzed for Tritium.
- b. Iodines: Gamma spectral analysis of charcoal cartridge and particulate filter on each release path.
- c. Particulates: Gamma spectral analysis of each particulate filter and charcoal cartridge for each release path. A four week per quarter composite of particulate filters for each release path for Strontium-89 and Strontium-90. One week per month particulate filter for each release path for gross alpha.
- d. Liquid Effluents: Gamma spectral analysis of each batch discharged, except composite analysis for Strontium-89, Strontium-90, Iron-55, Tritium, and Alpha.
- e. Solid Waste: Gamma spectral analysis of a representative sample of each waste shipment. Scaling factors established from off-site composite sample analyses to estimate concentration of non-gamma emitters. Low activity trash shipments, curie content estimated by dose rate measurement and application of appropriate scaling factors.
- f. Error Estimation Method: Overall error for sampling and analysis estimated by combining individual errors using error propagation methods. This process is composed of determinate and undeterminate errors.

Determinate - Pump flowrates, volume measurements and analysis collection yields Undeterminate - Random counting error estimated using accepted statistical calculations

SUPPLEMENTAL INFORMATION (continued)

5. Batch Releases

 $\langle \mathcal{T} \rangle$

	a. Liquid: Canal	Quarter 1	Quarter 2	Quarter 3	Quarter 4
	(1) Number of batch releases:	6.00E+00	1.00E+01	4.00E+00	1.60E+01
	(2) Total time period for batch release: (min)	1.03E+02	2.44E+02	1.32E+02	7.90E+02
	(3) Maximum time period for batch release: (min)	5.60E+01	8.00E+01	8.00E+01	1.63E+02
	(4) Average time period for batch release: (min)	1.72E+01	2.44E+01	3.33E+01	4.94E+01
.*	(5) Minimum time period for batch release: (min)	1.00E+00	4.00E+00	1.00E+00	3.00E+00
ι	(6) Total Activity Released (Ci)	2.92E-05	1.42E-04	4.24E-05	1.26E-01
	(7) Total Volume Released (liters)	1.85E+04	2.03E+04	3.95E+03	2.43E+05
	b. <u>Liquid: Non-Canal</u>			·	•
	(1) Number of batch releases:	1.00E+01	1.20E+01	1.20E+01	1.00E+01
	(2) Total time period for batch release: (min)	9.60E+00	4.32E+01	1.06E+02	2.35E+02
	(3) Maximum time period for batch release: (min)	1.80E+00	2.52E+01	4.68E+01	1.19E+02
	(4) Average time period for batch release: (min)	9.60E-01	3.60E+00	8.85E+00	2.35E+01
	(5) Minimum time period for batch release: (min)	6.00E-01	6.00E-01	1.20E+00	6.00E-01
	(6) Total Activity Released (Ci)	1.47E-05	5.76E-05	4.63E-05	2.15E-04
	(7) Total Volume Released (liters)	3.63E+03	1.64E+04	4.02E+04	8.91E+04

SUPPLEMENTAL INFORMATION (continued)

c. Gaseous:

There were no gaseous batch releases for this report period.

6. Abnormal Releases

a. [`]	Liquid:	Quarter 1	Quarter 2	Quarter 3	Quarter 4
	 (1) Number of releases: (2) Total activity released: 	NONE ⁻ NONE	NONE NONE	NONE NONE	NONE NONE
b.	Gaseous	~			
	 (1) Number of releases: (2) Total activity released: 	NONE NONE	NONE NONE	NONE NONE	NONE NONE

GASEOUS EFFLUENTS--SUMMATION OF ALL RELEASES

			UNIT	<u>QTR 1</u>	<u>QTR 2</u>	QTR 3	<u>QTR 4</u>	EST TOTAL <u>ERROR %</u>
A.	FIS	SSION AND ACTIVATION GASES						
	1.	Total Release	Ci	4.62E+01	2.67E+02	1.60E+02	1.50E+02	≤2.50E+01
	2. 3.	Average release rate for period Applicable ODCM Limit	μCi/sec %	5.87E+00 *	3.40E+01 *	2.02E+01 *	1.89E+01 *	
B.	IO	DINE-131						
	1. 2.	Total lodine-131 Average release rate for	Ci	2.04E-04	1.27E-03	9.26E-04	6.57E-04	≤2.50E+01
	3.	period Applicable ODCM Limit	μCi/sec %	2.59E-05 *	1.62E-04 *	1.17E-04 *	8.27E-05 *	
C.	РА	RTICULATES		. .				
	1.	Particulates with half-lives >8 days	Ci	1.01E-04	1.30E-04	1.48E-04	7.72E-05	≤3.60E+01
	2.	Average release rate for	μCi/sec	1.29E-05	1.65E-05	1.87E-05	9.71E-06	
	3. 4.	Applicable ODCM Limit Gross alpha radioactivity	% Ci	* 3.91E-07	* 3.83E-07	* 6.97E-07	* 3.71E-07	≤2.50E+01
D.	TR	ITIUM						•
	1.	Total Release	Ci	. 4.17E+00	3.11E+00	3.59E+00	3.09E+00	≤2.50E+01
	2. 3.	Average release rate for period Applicable ODCM Limit	μCi/sec %	5.30E-01 *	3.97E-01 *	4.51E-01 *	3.89E-01 *	
*Е.	OD	CENT OF APPLICABLE				· .		
)	FIS	SION AND ACTIVATION GASES						
	1. 2. 3.	Quarterly gamma air dose limit Quarterly beta air dose limit Yearly gamma air dose limit	% %	1.43E-02 9.22E-04 7.16E-03	1.16E-01 9.76E-03 5.80E-02	6:70E-02 5.46E-03 3.35E-02	6.67E-02 4.91E-03 3.34E-02	
	4. 5. 6.	Whole body dose rate limit Skin dose rate limit	% % %	4.16E-04 1.97E-03 3.99E-04	4.88E-03 1.26E-01 2.75E-02	2.73E-03 3.25E-02 7.15E-03	2.46E-03 1.09E-01 2.18E-02	
	HA WI	LOGENS, TRITIUM AND PARTIC TH HALF-LIVES >8 DAYS	ULATES					
	7. 8. 9.	Quarterly dose limit (organ) Yearly dose limit (organ) Organ dose rate limit	% % %	3.92E-02 1.96E-02 2.13E-05	1.65E-01 8.26E-02 5.27E-05	1.19E-01 5.97E-02 3.70E-05	8.96E-02 4.48E-02 2.71E-05	· ·

TABLE 1BGASEOUS EFFLUENTS--ELEVATED RELEASE

	CONTINUOUS MODE							
NUCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4			
1. Fission Gases								
Argon-41	Ci	3.63E+00	2.76E+00	3.83E+00	5.55E+00			
Krypton-85m	Ci	1.37E+01	2.08E+01	2.70E+01	3.38E+01			
Krypton-87	Ci	1.10E-01	3.68E+01	1:82E+01	4.86E+00			
Krypton-88	Ci	8.52E+00	3.71E+01	3.53E+01	4.20E+01			
Xenon-133	Ci	1.82E+01	2.19E+01	2.68E+01	3.31E+01			
Xenon-135	Ci	7.43E-01	7.22E+01	2.87E+01	5.21E+00			
Xenon-135m	Ci	1.96E-01	1.88E+01	4.00E+00	3.44E+00			
Xenon-137	Ci			4.85E+00	1.07E+01			
Xenon-138	Ci	7.28E-01	5.71E+01	1.18E+01	1.08E+01			
TOTAL	Ci	4.58E+01	2.67E+02	1.60E+02	1.49E+02			
2. Iodines								
lodine-131	Ci	7.51E-06	1.15E-03	8.31E-04	5.19E-04			
lodine-133	Ci	2.75E-05	1.72E-03	1.05E-03	5.42E-04			
lodine-135	Ci	· · · · ·	8.89E-04	1.11E-04	1.49E-04			
TOTAL	Ci	3.50E-05	3.76E-03	1.99E-03	1.21E-03			
3. <u>Particulates</u>	• .							
Manganese-54	Ci		2.24E-06	8.81E-07	4.37E-07			
Cobalt-60	Ci		*********	4.50E-07				
Strontium-89	Ci	4.74E-05	2.43E-05	1.93E-05	2.01E-05			
Strontium-90	Ci	2.75E-07	1.69E-07	6.35E-08	1.87E-05			
Cadmium-115m	Ci			3.90E-05				
Cesium-137	、 Ci		3.58E-07	****				
Barium-140	Ci			3.76E-06	1.82E-05			
TOTAL	Ci	4.77E-05	2.71E-05	6.34E-05	3.89E-05			
4. <u>Tritium</u>								
Hydrogen-3	Ci	4.26E-01	3.63E-01	6.05E-01	5.31E-01			

Note: There were no batch releases for this report period.

TABLE 1CGASEOUS EFFLUENTS--GROUND LEVEL RELEASES

		<u>CONTINUOUS MODE</u>					
NUCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4		
1. Fission Gases							
Xenon-133	Ci				4.53E-01		
Xenon-135	Ci	1.24E-01	8.85E-03		3.65E-01		
Xenon-135M	Ci	2.33E-01			*****		
Xenon-138	Ci		7.58E-02		*		
TOTAL	Ci	3.57E-01	8.47E-02		8.18E-01		
2. Iodines		,					
	0.						
Iodine-131	Ci	1.96E-04	1.23E-04	9.54E-05	1.38E-04		
Iodine-133	Ci	7.12E-04	3.99E-04	2.24E-04	4.10E-04		
TOTAL	Ci	9.08E-04	5.22E-04	3.19E-04	5.48E-04		
3. <u>Particulates</u>	·						
Chromium-51 /	Ci		1.28E-05				
Manganese-54	Ci	2.25E-05	2.73E-05	3.07E-06			
Cobalt-58	Ci	1.83E-06					
Iron-59	Ci		2.01E-05				
Cobalt-60	Ci	1.07E-05	1.48E-05	1.62E-06			
Zinc-65	Ci	5.75E-06	6.39E-06				
Strontium-89	Ci	1.12E-05	2.06E-05	5.77E-05	2.99E-05		
Strontium-90		1.46E-06	5.21E-07	3.20E-06	3.82E-06		
Barlum-140	CI			1.94E-05	4.60E-06		
TOTAL	Ci	5.34E-05	1.03E-04	8.50E-05	3.83E-05		
4. <u>Tritium</u>							
Hydrogen-3	Ci	3.74E+00	2.75E+00	2.98E+00	2.56E+00		

Note: There were no batch releases for this report period.

TABLE 2A LIQUID EFFLUENTS--SUMMATION OF ALL RELEASES

			<u>UNIT</u>	<u>OTR 1</u>	<u>QTR 2</u>	<u>QTR 3</u>	<u>QTR 4</u>	EST TOTAL ERROR %
A.	FIS	SION AND ACTIVATION PROD	UCTS					
	1. 2.	Total Release (not including tritium, gases and alpha) Average diluted concentration	Ci	NONE	NONE	NONE	1.72E-05	≤2.50E+01
	3.	during period Applicable ODCM Limit	µCi/ml %	NONE	NONE	NONE	1.72E-11 *	
B.	TR	ITIUM						
	1. 2.	Total Release Average diluted concentration	Ci	4.39É-05	2.00E-04	8.87E-05	1.26E-01	≤2.50E+01
	3.	during period (Note 1) Applicable ODCM Limit	µCi/ml %	6.65E-07 *	1.58E-06 *	1.05E-06 *	7.37E-07 *	
C.	DIS	SOLVED AND ENTRAINED GAS	SES		,			•
	1. 2.	Total Release Average diluted concentration	Ci	NONE	NONE	NONE	5:36E-04	≤2.50E+01
	3.	during period Applicable ODCM Limit	µCi/ml %	NONE *	NONE *	NONE *	3.90E-10	
D.	GR	OSS ALPHA RADIOACTIVITŶ	•					
,	1.	Total Release	Ci	NONE	NONE	NONE	2.44E-06	≤4.20E+01
E.	VO (PR	LUME OF WASTE RELEASED NOR TO DILUTION)	liters	2.22E+04	3.67E+04	4.42E+04	3.33E+05	
F.	VO US	LUME OF DILUTION WATER ED DURING PERIOD	liters	1.35E+08	3.37E+08	1.97E+08	1.01E+09	
∗G.	PEI OD	RCENT OF APPLICABLE			1			·
	1. 2. 3. 4.	Quarterly Whole Body Dose Quarterly Organ Dose Annual Whole Body Dose Annual Organ Dose	% · % %	3.05E-04 9.16E-05 1.53E-04 4.58E-05	6.50E-04 1.95E-04 3.25E-04 9.75E-05	1.58E-04 4.75E-05 7.92E-05 2.38E-05	1.97E-04 5.78E-05 9.85E-05 2.89E-05	

(Note 1) Concentration includes summation from diluted and undiluted values from Canal and Non-Canal releases (Table 2B).

TABLE 2BLIQUID EFFLUENTS CANAL

		BAT <u>CH MODE</u>					
NUCLIDES RELEASED	UNIT QUARTER 1		QUARTER 2	QUARTER 3	QUARTER 4		
1. Fission and Activation Products							
Iron-55 Strontium-89 Strontium-90	Ci Ci ∢ Ci	 	 	 	1.17E-05 5.05E-06 5.44E-07		
TOTAL	Ci	<u> </u>			1.73E-05		
2. <u>Tritium</u>			·	ź			
Hydrogen-3	Ci	2.92E-05	1.42E-04	4.24E-05	1.26E-01		
3. Dissolved and Entrained Gases		· .					
Xenon133	Ci				5.36E-04		
TOTAL					5.36E-04		

Note: There were no continuous mode discharges during this report period.

TABLE 2B (SUPPLEMENT)LIQUID EFFLUENTS NON-CANAL

			<u>BATC</u>	<u>CH MODE</u>	•
NUCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
1. Fission and Activation Produc	<u>ets</u>				
NONE	Ci	1			
2. <u>Tritium</u>		(
Hydrogen-3	Ci	1.47E-05	5.76E-05	4.63E-05	2.15E-04
3. Dissolved and Entrained Gase	<u>s</u>	- -			
NONE	Ci				

Note: There were no continuous mode discharges during this report period.

Λ

TABLE 3ASOLID WASTE AND IRRADIATED FUEL SHIPMENTS

A. SOLID WASTE SHIPPED OFFSITE FOR BURIAL OR DISPOSAL (NOT IRRADIATED FUEL)

					ESt. Total
Type of Waste	Unit	Class A	Class B	Class C	Error %
a. Spent resins, filter sludges	m^3	0.00E+00	0.00E+00	0.00E+00	0.00E+00
evaporator bottoms, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
b. Dry compressible waste,	 m^3	0.00E+00	0.00E+00	0.00E+00	0.00E+00.
contaminated equipment, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
c. Irradiated components,	m^3	0.00E+00	0.00E+00	5.00E-02	1.00E+01
control rods, etc.	Ci	0.00E+00	0.00E+00	7.47E-02	1.00E+01
d. Other: Dry compressible	m^3	4.85E+02	2.19E+01	5.71E-03	1.00E+01
waste, contaminated equipment, spent resins for volume reduction.	Ci	6.86E+01	5.21E+02	5.33E+02	1.00E+01.
	 Type of Waste a. Spent resins, filter sludges evaporator bottoms, etc. b. Dry compressible waste, contaminated equipment, etc. c. Irradiated components, control rods, etc. d. Other: Dry compressible waste, contaminated equipment, spent resins for volume reduction. 	Type of WasteUnita. Spent resins, filter sludgesm^3evaporator bottoms, etc.Cib. Dry compressible waste,m^3contaminated equipment, etc.Cic. Irradiated components,m^3control rods, etc.Cid. Other: Dry compressiblem^3waste, contaminated equipment,cispent resins for volume reduction.Ci	Type of WasteUnitClass Aa. Spent resins, filter sludgesm^30.00E+00evaporator bottoms, etc.Ci0.00E+00b. Dry compressible waste,m^30.00E+00contaminated equipment, etc.Ci0.00E+00c. Irradiated components,m^30.00E+00control rods, etc.Ci0.00E+00d. Other: Dry compressiblem^34.85E+02waste, contaminated equipment,Ci6.86E+01spent resins for volume reduction.Ci6.86E+01	Type of WasteUnitClass AClass Ba. Spent resins, filter sludgesm^30.00E+000.00E+00evaporator bottoms, etc.Ci0.00E+000.00E+00b. Dry compressible waste,m^30.00E+000.00E+00contaminated equipment, etc.Ci0.00E+000.00E+00c. Irradiated components,m^30.00E+000.00E+00c. Irradiated components, control rods, etc.m^30.00E+000.00E+00d. Other: Dry compressiblem^34.85E+022.19E+01waste, contaminated equipment, spent resins for volume reduction.Ci6.86E+015.21E+02	Type of Waste a. Spent resins, filter sludges evaporator bottoms, etc.Unit m^3 CiClass A 0.00E+00 0.00E+00Class B 0.00E+00 0.00E+00Class C 0.00E+00 0.00E+00b. Dry compressible waste, contaminated equipment, etc.m^3 Ci0.00E+00 0.00E+000.00E+00 0.00E+000.00E+00 0.00E+00c. Irradiated components, control rods, etc.m^3 Ci0.00E+00 0.00E+000.00E+00

Estimate of Major Nuclide Composition (by type of waste)
 a. Spent resins, filter sludges, evaporator bottoms, etc.

NONE

b. Dry compressible waste, contaminated equipment, etc.

NONE

c. Irradiated components, control rods, etc.

Isotope	Percent	Curies		Isotope	Percent	<u>Curies</u>	
Hydrogen-3	2.02E-02	1.51E-05	Е	Iron-59	1.37E-02	1.02E-05	Е
Manganese-54	3.20E+00	2.39E-03	Е	Nickel-59	1.23E-02	9.16E-06	Έ
Iron-55	4.77E+01	3.56E-02	Е	Cobalt-60	4.68E+01	3.50E-02	Е
Cobalt-58	3.98E-01	2.97E-04	Е	Nickel-63	1.86E+00	1.39E-03	Е

d. Other: Dry compressible waste, contaminated equipment, spent resins for volume reduction.

Isotope	Percent	<u>Curies</u>		Isotope	Percent	Curies	
Hydrogen-3	1.05E-01	1.18E+00	Е	Zinc-65	6.37E+00	7.15E+01	Е
Carbon-14	5.20E-02	5.83E-01	Е	Strontium-90	8.35E-02	9.37E-01	E
Manganese-54	7.37E+00	8.27E+01	Е	Antimony-125	7.20E-02	8.08E-01	Е
Iron-55	6.68E+01	7.49E+02	Е	Cesium-134	4.71E-01	5.28E+00	E
Cobalt-58	4.26E-02	4.78E-01	Е	Cesium-137	1.47E+00	1.65E+01	Е
Cobalt-60	1.57E+01	1.76E+02	E	Cesium-144	6.75E-02	7.58E-01	Е
Nickel-63	1.44E+00	1.61E+01	Е				

(E- Estimated M- Measured)

Percentage of nuclides and total activities are based on a combination of direct measurements and scaling for non-gamma emitting nuclides.

TABLE 3A (continued)SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

3. Solid Waste Disposition

No. of Shipments	Mode of Transportation	Destination
8	Truck	* Duratek Oak Ridge, TN
15	Truck	* Studsvik Erwin, T

*- Volume Reduction Facility

B. IRRADIATED FUEL SHIPMENTS (Disposition)

No. of Shipments	Mode of Transportation	,	Destination
			· .
NONE			

TABLE 3BSOLID WASTE AND IRRADIATED FUEL SHIPMENTS

NRC CLASS A

SOURCE OF <u>WASTE</u>	PROCESSING <u>EMPLOYED</u>	CONTAINER <u>VOLUME</u>	TYPE OF <u>CONTAINER</u>	NUMBER OF CONTAINERS
Spent Resins, Filter Sludges, evaporator Bottoms, etc.	Air Drying Non-compacted	205.8 ft^3	HIC	4
Spent Resins, Filter Sludges, evaporator Bottoms, etc.	Air Drying Non-compacted	120.3 ft^3	HIC	1
Dry compressible Waste (DAW), Contaminated Equipment, etc.	Non-compacted	1280 ft^3	STC	10
Dry compressible Waste (DAW), Contaminated Equipment, etc.	Non-compacted	2560 ft^3	STC	1
Dry compressible Waste(DAW) Contaminated Eqiupment, etc.	Non-compacted	96 ft^3	STC	12
Contaminated Oil	Non-compacted	7.5 ft^3	STC	21
Dry compressible Waste(DAW)	Non-compacted	1033.5 ft^3	STC	2

Contaminated Equipment

B. NRC CLASS B

SOURCE OF <u>WASTE</u>	PROCESSING EMPLOYED	CONTAINER <u>VOLUME</u>	TYPE OF <u>CONTAINER</u>	NUMBER OF <u>CONTAINERS</u>
Sludges, evaporator Bottoms, etc.	Air Drying Non-compacted	205.8 ft^3	HIC	2
Spent Resins, Filter Sludges, evaporator Bottoms, etc.	Air Drying Non-compacted	120.3 ft^3	HIC	2
Dry compressible Waste(DAW) Contaminated Equipment	Non-compacted	120.3 ft^3	HIC	1
C. NRC CLASS C				1
SOURCE OF <u>WASTE</u>	PROCESSING EMPLOYED	CONTAINER <u>VOLUME</u>	TYPE OF <u>CONTAINER</u>	NUMBER OF CONTAINERS
Dry compressible Waste(DAW) Contaminated Equipment	Non-compacted	120.3 ft^3	HIC	2
Irradiated Hardware	Non-compacted	120.3 ft^3	STC	1
Solidification Agent:	NONE			

HIC- High Integrity Container STC-Strong Tight Container

ATTACHMENT NO.1

CHANGES TO THE OFFSITE DOSE CALCULATION MANUAL (ODCM)

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 6.2.3, changes made to the Offsite Dose Calculation Manual (ODCM) during the reporting period shall be included in the Annual Radioactive Effluent Release Report.

There were no changes to the Offsite Dose Calculation Manual (ODCM).

ATTACHMENT NO. 2

SUMMARY OF CHANGES TO THE PROCESS CONTROL PROGRAM

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 6.2.3, changes made to the Process Control Program (PCP) during the reporting period shall be included in the Annual Radioactive Effluent Release Report.

Revisions to the Performance Reference procedure FO-OP-023-41802, Waste Transfer and Bead Resin/Activated Carbon Dewatering Procedure for Energy Solutions' 14-215 or Smaller liners at James A. FitzPatrick Nuclear Plant was made and approved on 9/17/07. These revisions do not reduce the overall conformance of the solidified waste product to existing criteria for solid waste. Listed below is a brief summary of changes incorporated in this revision.

- 1) Duratek changed to Energy Solutions throughout the procedure.
- 2) Changed to allow non-bed and carbon media to offsite processing facility.
- 3) Changed to allow Quality Assurance hold points to be waived if being sent to offsite processing facility.
- 4) Added caution to observe for traces of oil or water in the resin to terminate the process.
- 5) Increased the number of dewatering cycles from 3 to 5 to improve dewatering process.
- 6) Changed routing of completion records to Energy Solutions project manager if processing for direct burial.

ATTACHMENT NO. 3

SUMMARY OF CHANGES TO THE ENVIRONMENTAL MONITORING AND DOSE CALCULATION LOCATIONS

In accordance with the James A. FitzPatrick Nuclear Power Plant Off Site Dose Calculation Manual (ODCM), Part 1, Sections 6.2.3 a listing of new locations for dose calculation and/or environmental monitoring identified by the land use census shall be included in the Annual Radioactive Effluent Release Report.

CHANGES IN ENVIRONMENTAL MONITORING LOCATIONS

CHANGES TO THE REMP PROGRAM

The following changes were implemented during the 2007 sampling program:

A. Food Product Sampling Program

During the reporting period, one new food product location was added and one food product location was removed from the Environmental Monitoring locations. These locations are used to implement the requirements of the ODCM, Part 1, Table 5.1-1. Sample locations selected were based on the 2007 annual land use census and were utilized to implement the 2007 food product requirements.

B. Milk Sampling Program

During the reporting period, one of the milk sample locations ceased millk production in May of 2007. Samples were obtained from Sample Location #4 during April and May of 2007. This location was used to implement the requirements of ODCM, Part 1, Table 5.1-1 even though its distance from the plant was greater than 5 miles.

C. Ground Water Monitoring Program

During the reporting period, 5 ground water monitoring wells were drilled along the northern edge of the site property. Samples obtained from these wells were counted for tritium. These wells are used to implement the NEI Ground Water Protection Initiative.

NEW LOCATIONS FOR DOSE CALCULATIONS

During the report period, no changes in Dose Calculation Receptor Locations were required based on the results of the land use census.

ATTACHMENT NO. 4

DEVIATIONS FROM THE REQUIRED ENVIRONMENTAL SAMPLING SCHEDULE

In accordance with the James A. FitzPatrick Nuclear Power Plant Off Site Dose Calculation Manual (ODCM), Part 1, Section 6.2.7 the cause for the unavailability of any environmental samples required during the report period shall be included in the Annual Radioactive Effluent Release Report.

The following reports samples that were a deviation from the requirements of ODCM Part 1, Table 5.1-1. ODCM Part I, Section 5.1.1.c.1 allows for deviations from the program due to hazardous conditions, seasonal unavailability, theft, uncooperative residents, or to malfunction of automatic sampling equipment.

A. ODCM Program Deviations

The following are deviations from the program specified by the ODCM:

- 1. Environmental Air sample station R-2 offsite flow control valve was found chattering during the sample period of 1/29/07 to 2/6/07. The volumetric flow rate was outside of the acceptable range of the procedure. The sample pump was replaced and flowrate returned to acceptable range. Total air sample station out of service time was 0.25 hours.
- 2. The air sampling pump at the R-1 and R-2 Environmental Sampling Station was inoperable for approximately 6 hours during the sample period of 7/3/07 to 7/10/07. The air sample pump was running at the time of sample collection. The sample pump out of service time was determined based on the sample pump run time integrator. The inoperability of the pump was due to loss of power to the sampler. No corrective actions were required to restore unit to service.
- 3. Continuous sampling was not maintained at Environmental Air sample stations R-1 Offsite and R-2 Offsite. During the sample period from 9/11/07 to 9/18/07, a period of 3.7 hours was lost due to a power outage. Pumps were found running during the weekly sample change out..
- 4. A loss of sample collection occurred at the R-1 Offsite station for a duration of 1.9 hrs and R-2 Offsite station for a duration of 1.2 hrs. The loss of sample is based on the station's air pump integrating time and was determined to be due to a power outage in the area.

B. Air Sampling Station Operability Assessment

The ODCM required air sampling program consists of 5 individual sampling locations. The collective operable time period for the air monitoring stations was 43,790 hours out of a possible 43,800 hours. The air sampling availability factor for the report period was 99.98%.

ATTACHMENT NO. 5

ANNUAL SUMMARY OF HOURLY METEOROLOGICAL DATA

The James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1, Radiological Controls (REC) Section 6.2 and 6.2.2 states in part: The Annual Radioactive Effluent Release Report submitted prior to May 1 of each year may include an annual summary of meteorological data collected over the previous year. If the meteorological data is not included, the licensee shall retain it on file and provide it to the U.S. Nuclear Regulatory Commission upon request. In accordance with the aforementioned ODCM requirement, meteorological data is not included in this report. It is retained on file and is available upon request.

ATTACHMENT NO. 6

MAJOR MODIFICATIONS TO RADIOACTIVE LIQUID, GASEOUS AND SOLID WASTE TREATMENT SYSTEMS

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 7.0, Major Modifications to Radioactive Waste Treatment Systems (liquid, gaseous and solid) shall be reported in the Annual Radioactive Effluent Release Report for the period in which the modification is completed and made operational.

There were no major modifications to any liquid, gaseous, or solid radioactive waste treatment systems.

ATTACHMENT NO. 7

ONSITE GROUND WATER MONITORING

A) Gamma Isotopic Monitoring

Monitoring Wells (5-9) were analyzed to below the required lower limits of detection in accordance with the Offsite Dose Calculation Manual (ODCM) Part 1, Table 2.2-1. These values are as follows:

Radionuclide	LLD Value	Radionuclide	LLD Value
	(μCi/ml)		(µCi/ml)
Manganese-54	5.0E-7	lodine-131	1.0E-6
Cobalt-58	5.0E-7	Cesium-134	5.0E-7
Iron-59	5.0E-7	Cesium-137	5.0E-7
Cobalt-60	5.0E-7	Cerium-141	5.0E-5
Zinc-65	5.0E-7	Cerium-144	5.0E-5
Molybdenum-99	5.0E-5		,

There were no plant related nuclides detected in the samples.

B) Tritium Monitoring

Monitoring Wells (5-9) were analyzed for tritium to below the required lower limit of detection in accordance with the Offsite Dose Calculation Manual (ODCM) of 3000 pCi/L.

The results are as follows:

Well	Lower Limit of Detection pCi/L	Sample Result pCi/L
5	1000	<909
6	1000	<909
. 7	1000	<909
8	1000	<909
Í 9	1000	<909

ADDENDUM 1

ASSESSMENT OF RADIATION DOSES TO THE PUBLIC JANUARY - DECEMBER 2007

1. INTRODUCTION

The James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls, requires an assessment of the radiation doses to the public due to radioactive liquid and gaseous effluents. This assessment of doses to the public is based on accepted methodologies found in the Offsite Dose Calculation Manual (ODCM).

DOSE LIMITS

2.

A. <u>DOSE FROM LIQUID EFFLUENTS</u> (ODCM, Part 1, REC 2.3)

Applicability

Applies to doses from radioactive material in liquid effluents.

Objective

To ensure that the dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The dose to a member of the public from radioactive materials released from the plant in liquid effluents to unrestricted areas shall be limited as follows:

- 1. During any calendar quarter, limited to less than or equal to 1.5 mrem to the whole body and to less than or equal to 5 mrem to any organ.
- 2. During any calendar year, limited to less than or equal to 3 mrem to the whole body and to less than or equal to 10 mrem to any organ.

B. <u>GASEOUS DOSE RATES</u> (ODCM, Part 1, REC 3.2)

Applicability

Applies to the radiation dose from radioactive material in gaseous effluents.

ADDENDUM 1 (continued)

Objective

To ensure that the dose rates at or beyond the site boundary from gaseous effluents do not exceed the annual dose limits of 10 CFR 20, for unrestricted areas.

<u>Specifications</u>

The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluents shall be limited as follows:

- 1. Less than or equal to 500 mrem/year to the whole body and less than or equal to 3000 mrem/year to the skin from noble gases; and,
- 2. Less than or equal to 1500 mrem/year to any organ from Iodine-131, Iodine-133, Tritium and for radioactive materials in particulate form with half-lives greater than 8 days (inhalation pathway only).

C. <u>AIR DOSE, NOBLE GASES</u> (ODCM, Part 1, REC 3.3)

Applicability

Applies to the air dose due to noble gases in gaseous effluents.

Objective

To ensure that the noble gas dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The air dose to areas at or beyond the site boundary from noble gases released from the plant in gaseous effluents shall be limited:

- 1. During any calendar quarter, to less than or equal to 5 mrad from gamma radiation, and less than or equal to 10 mrad from beta radiation; and,
- 2. During any calendar year, to less than or equal to 10 mrad from gamma radiation and less than or equal to 20 mrad from beta radiation.

ADDENDUM 1 (continued)

D. <u>DOSE DUE TO IODINE-131, IODINE-133, TRITIUM AND</u> <u>RADIONUCLIDES IN PARTICULATE FORM</u> (ODCM, Part 1, REC 3.4)

Applicability

Applies to the cumulative dose from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days in gaseous effluents.

<u>Objective</u>

To ensure that the dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The dose to a member of the public at or beyond the site boundary from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days released from the plant in gaseous effluents shall be limited:

- 1. During any calendar quarter to less than or equal to 7.5 mrem to any organ; and,
- 2. During any calendar year to less than or equal to 15 mrem to any organ.

E. <u>TOTAL DOSE FROM URANIUM FUEL CYCLE</u> (ODCM, Part 1, REC 4.0)

Applicability

Applies to radiation dose from releases of radioactivity and radiation from uranium fuel cycle sources.

Objective

To ensure that the requirements of 40 CFR 190 are met.

ADDENDUM 1 (continued)

Specifications

The dose or dose commitment to any member of the public, due to releases of radioactivity and radiation, from uranium fuel cycle sources shall be limited as follows:

- 1. Less than or equal to 25 mrem/year to the whole body; and,
- 2. Less than or equal to 25 mrem/year to any organ except the thyroid which shall be limited to less than or equal to 75 mrem/year.

DOSE ASSESSMENT

3.

A. <u>METHODOLOGY</u>

The assessment of radiation doses to the public due to radioactive liquid and gaseous effluents is performed in accordance with the ODCM. The ODCM is based on methodologies and models suggested by the "Guidance Manual For Preparation of Radiological Effluent Technical Specifications for Nuclear Power Plants" (NUREG-0133) and "Calculation of Annual Doses to Man from Routine Releases of Reactor Effluents for the purpose of Evaluating Compliance with 10CFR50, Appendix I" (Regulatory Guide 1.109).

B. ASSUMPTIONS

Dose calculations are performed using formulas and constants defined in the ODCM. Specific radioactive release activities used in the dose calculations are listed in the Annual Radioactive Effluent Release Report (1.21 Report) for the period of January 1, 2007 to December 31, 2007. Historical meteorological data was used to generate tables of average dispersion factors. Locations of interest were identified from the 2007 land use census. Dispersion factors and locations of interest used in performing the dose calculations are listed in Table 2.

C. ASSESSMENT RESULTS SUMMARY

The calculated doses to the public due to radioactive effluents are listed in Table 1. The calculated doses are small fractions of their respective dose limits.

ADDENDUM 1 (continued)

40 CFR 190 DOSE ASSESSMENT

A. <u>METHODOLOGY</u>

4.

Evaluation to demonstrate compliance with the 40 CFR 190 dose limits must be performed when the doses calculated for 10 CFR 50 compliance exceed twice their respective limits. When additional dose assessment is required to demonstrate compliance with 40 CFR 190 it is performed in accordance with the ODCM.

B. <u>RESULTS SUMMARY</u>

The cumulative dose contribution from liquid and gaseous effluents for this report period were calculated and are listed in Table 1. The cumulative dose contribution from direct radiation from the reactor unit and from radwaste storage tanks is measured by environmental thermoluminescent dosimeters for the report period. This data is contained in the Annual Environmental Operating Report. The calculated doses from liquid and gaseous effluents are less than twice their respective 10 CFR 50 limits, therefore, additional calculations are not necessary to demonstrate compliance with 40 CFR 190 dose limits (ODCM, Part 1, REC 4.1.1.c)

ADDENDUM 1 (continued)

			<u> </u>		
	3* *	A. LIQU	IDS	· ·	
<u>QUARTER</u>	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>ANNUAL</u>
	(a)	(a)	(a)	(a)	(a)
Organ (mrem) % of Limit	4.58E-06 9.16E-05	9.75E-06 1.95E-04	2.38E-06 4.75E-05	2.89E-06 5.78E-05	1.96E-05 1.96E-04
	(b)	(b)	(b)	(b)	(b)
Whole Body (mrem) % of Limit	4.58E-06 3.05E-04	9.75E-06 6.50E-04	2.38E-06 1.58E-04	2.96E-06 1.97E-04	1.98E-05 6.56E-04

TABLE 1ANNUAL DOSE ASSESSMENT 2007

(a) Dose to the Child Liver primarily by the potable water pathway.

(b) Dose to the Child Whole Body primarily by the potable water pathway.

	* : ,	B. NOBLE	GASES		
QUARTER	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	ANNUAL
Total Body (mrem/yr)	9.84E-03	6.30E-01	1.62E-01	5.44E-01	6.30E-01
% of Limit	1.97E-03	1.26E-01	3.25E-02	1.09E-01	1.26E-01
Skin (mrem/yr)	1.20E-02	8.24E-01	2.15E-01	6.53E-01	8.24E-01
% of Limit	3.99E-04	2.75E-02	7.15E-03	2.18E-02	2.75E-02
Gamma (mrad)	7.16E-04	5.80E-03	3.35E-03	3.34E-03	1.32E-02
% of Limit	1.43E-02	1.16E-01	6.70E-02	6.67E-02	1.32E-01
Beta (mrad)	9.22E-05	9.76E-04	5.46E-04	4.91E-04	2.10E-03
% of Limit	9.22E-04	9.76E-03	5.46E-03	4.91E-03	1.05E-02

ADDENDUM 1 (continued)

			., '		
1	C. IOI	DINES AND	PARTICUL	ATES	
QUARTER	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	ANNUAL
	(a)	(b)	(b)	(b)	(b)
Organ (mrem) % of Limit	2.94E-03 3.92E-02	1.24E-02 1.65E-01	8.96E-03 1.19E-01	6.72E-03 8.96E-02	3.10E-02 2.07E-01
	(a)	(a)	(a)	(a)	(a)
Organ Dose Rate (mrem/yr)	3.20E-04	7.91E-04	1.50E-03	4.06E-04	1.50E-03
% of Limit	2.13E-05	5.27E-05	3.70E-05	2.71E-05	3.70E-05

TABLE 1ANNUAL DOSE ASSESSMENT 2007

(a) Dose to the Child Thyroid primarily by the vegetation pathway.

(b) Dose to the Infant Thyroid primarily by the goats milk pathway.

· · · · · · • •

1 7 1

ADDENDUM 1 (continued)

TABLE 2

METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

	GEOGRAPHIC	GEOGRAPHIC		
RECEPTOR	LOCATION		DISPERSION	N FACTOR
A. IODINE &	DISTANCE/	RELEAS	E X/Q	D/Q
PARTICULATES	DIRECTION	POINT	(sec/m^3)	(l/m^2)
1. Garden	0.90 mi @ 83°E	ST	2.83E-08*	1.75E-09
Grazing Season	0.90 mi @ 83°E	RX	2.02E-07*	5.01E-09
Cary	0.90 mi @ 83°E	TB	1.83E-07*	4.80E-09
Location No. 78	0.90 mi @ 83°E	RF	2.02E-07*	5.01E-09
	0.90 mi @ 83°E	RW	3.21E-07*	5.76E-09
2. Meat	1.18 mi @ 127°SE	ST	1.72E-08*	6.80E-10
Grazing Season	1.18 mi @ 127°SE	RX	5.36E-08*	1.30E-09
Parkhurst	1.18 mi @ 127°SE	TB	5.14E-08*	1.27E-09
Location No. 26	1.18 mi @ 127°SE	RF	5.36E-08*	1.30E-09
· · · ·	1.18 mi @ 127°SE	RW	9.12E-08*	1.46E-09
3. Cow	2.50 mi @ 139°SE	ST	1.67E-08*	2.65E-10
Grazing Season	2.50 mi @ 139°SE	RX	2.76E-08*	4.14E-10
France	2.50 mi @ 139°SE	TB	2.71E-08*	4.07E-10
Location No. 10	2.50 mi @ 139°SE	RF	2.76E-08*	4.14E-10
	2.50 mi 🥘 139°SE	RW	4.15E-08*	4.36E-10
4. Goat (D/Q)	3.62 mi @ 113°ESE	ST		2.28E-10
Grazing Season	3.62 mi @ 113°ESE	RX		3.40E-10
Showers	3.62 mi @ 113°ESE	TB		3.33E-10
Location No. 71	3.62 mi @ 113°ESE	RF		3.40E-10
	3.62 mi @ 113°ESE	RW		3.49E-10
5. Goat (X/Q)	2.64 mi @ 152°SSE	ST	1.94E-08*	
Grazing Season	2.64 mi @ 152°SSE	RX	2.58E-08*	
Nickolas	2.64 mi @ 152°SSE	TB	2.57E-08*	
Location No. 61	2.64 mi @ 152°SSE	RF	2.58E-08*	
	2.64 mi @ 152°SSE	RW	3.59E-08*	

-11

ADDENDUM 1 (continued)

TABLE 2

METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

RECEPTOR	GEOGRAPHIC LOCATION	ATMOSPHERI DISPERSION FACT		
A. IODINE & PARTICULATES	DISTANCE/ DIRECTION	RELEASE POINT	Z X/Q (sec/m3)	D/Q (l/m2)
6. Resident Annual Average				
a. Inhalation ⁽²⁾	1.55 mi @ 90°E ⁽¹⁾	ST	2.99E-08	
Cary	0.90 mi @ 83°E	RX	2.07E-07	
Location No. 78	0.90 mi @ 83°E	ТВ	1.88E-07	- <u></u> ,
· .	0.90 mi @ 83°E	RF	2.07E-07	
	0.90 mi @ 83°E	RW	3.06E-07	
b. Deposition $^{(3)}$	0.71 mi @ 118°ESE	ST		1.60E-09
Whaley	0.71 mi @ 118°ESE	RX		5.52E-09
Location No. 199	0.71 mi @ 118°ESE	TB		5.30E-09
	0.71 mi @ 118°ESE	RF		5.52E-09
	0.71 mi @ 118°ESE	RW		6.28E-09
B. NOBLE GASES	·······.			
1. Air Dose	1.55 mi @ 90°E ⁽¹⁾	ST	2.99E-08	
Annual Average	0.60 mi @ 90°E	ST(fc)	1.16E-07	
Site Boundary	0.60 mi @ 90°E	RX	3.58E-07	
	0.60 mi @ 90°E	TB	3.19E-07	
	0.60 mi @ 90°E	RF	3.58E-07 [.]	
	0.60 mi @ 90°E	RW	5.39E-07	
				•
2. Total Body	0.60 mi @ 90°E	ST(fc)	1.16E-07	
Annual Average	0.60 mi @ 90°E	RX	3.58E-07	
Site Boundary	0.60 mi @ 90°E	TB	3.19E-07	
	0.60 mi @ 90°E	RF	3.58E-07	
	0.60 mi @ 90°E	RW	5.39E-07	

ADDENDUM 1 (continued)

TABLE 2

METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

RECEPTOR	GEOGRAPHIC LOCATION	D	ATMOS ISPERSIOI	SPHERIC** N FACTOR
B. NOBLE GASES (continued)	DISTANCE/ DIRECTION	RELEASE POINT	X/Q (sec/m3)	D/Q (l/m2)
3. Skin	1.55 mi @ 90°E	ST	2.99E-08	
Annual Average	0.60 mi @ 90°E	ST(fc)	1.16E-07	
Site Boundary	0.60 mi 🤕 90°E	RX	3.58E-07	
·	0.60 mi @ 90°E	ТВ	3.19E-07	
	0.60 mi @ 90°E	RF	3.58E-07	
	0.60 mi @ 90°E	RW	5.39E-07	

* Tritium Dose Calculation

* Based on ODCM X/Q, D/Q Values Rev. 08

(1) Highest Sector Average X/Q in a populated area, not an identified residence.

(2) Inhalation uses Annual Average X/Q values. All other receptors use grazing season meteorology.

(3) Deposition uses Annual Average D/Q values. All other receptors use grazing season meteorology.

ST = Main Stack

RX = Reactor Building Vent

TB = Turbine Building Vent

RF = Refuel Floor Vent

RW = Radwaste Building Vent

fc = Finite Cloud