

Entergy Nuclear Northeast Entergy Nuclear Operations, Inc. James A. FitzPatrick NPP P.O. Box 110 Lycoming, NY 13093 315-342-3840

Chris M. Adner Regulatory Assurance Manager - JAF

JAFP-15-0051 April 29, 2015

United States Nuclear Regulatory Commission Attn: Document Control Desk Washington, D.C. 20555-0001

SUBJECT:

2014 Annual Radioactive Effluent Release Report James A. FitzPatrick Nuclear Power Plant

Docket No. 50-333 License No. DPR-59

Dear Sir or Madam:

This letter transmits the James A. FitzPatrick Nuclear Power Plant's (JAF) Annual Radioactive Effluent Release Report, for the period of January 1, 2014 through December 31, 2014. The enclosure is submitted in accordance with the Reporting Requirements of the Technical Specifications, Section 5.6.3 and Appendix H of the Technical Requirements Manual, "Offsite Dose Calculation Manual (ODCM)," Part 1 Section 6.2, Radioactive Effluent Release Report.

This report (Enclosure) includes, as an Addendum, an Assessment of the Radiation Doses to the Public due to the radioactive liquid and gaseous effluents released during the 2014 calendar year. The format used for the effluent data is outlined in Appendix B of Regulatory Guide 1.21, Revision 1. Distribution is in accordance with Regulatory Guide 10.1, Revision 4.

There are no commitments contained in this letter.

If you have any questions concerning the enclosed report, please contact Mr. Michael Ponzo, Chemistry Manager, at (315)349-6168.

Sincerely.

Chris M. Adner Regulatory Assurance Manager - JAF

CMA/MP/ds

Annual Radioactive Effluent Release Report, January 1 - December 31, 2014 Enclosure:

cc: next page

cc:

Regional Administrator, Region I U. S. Nuclear Regulatory Commission 2100 Renaissance Blvd., Suite 100 King of Prussia, PA 19406-2713

Resident Inspector's Office U.S. Nuclear Regulatory Commission James A. FitzPatrick Nuclear Power Plant P.O. Box 136 Lycoming, NY 13093

Mr. Douglas Pickett, Senior Project Manager Plant Licensing Branch I-1 Division of Operating Reactor Licensing Office of Nuclear Reactor Regulation U.S. Nuclear Regulatory Commission Mail Stop O-8-C2A Washington, DC 20555-0001

M. Ponzo (CHEM/JAF) B. Landers (CHEM/JAF) K. Stoffle (NMP)

Document Contents: 001 Transmittal Letter, JAFP-15-0051 with enclosure JAFP-15-0051 Enclosure

2014 Annual Radioactive Effluent Release Report

(39 Pages)

JANUARY 1, 2014 - DECEMBER 31, 2014

DOCKET NO. 50-333

LICENSE NO. DPR-59

SUPPLEMENTAL INFORMATION

FACILITY: JAFNPP LICENSEE: ENTERGY NUCLEAR OPERATIONS, INC.

1. Offsite Dose Calculation Manual Part 1 Radiological Controls

- a. Fission and Activation Gases:
 - (1) The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluent shall be limited as follows:
 - (a) Less than or equal to 500 mrem/year to the whole body and less than or equal to 3000 mrem/year to the skin from noble gases.
 - (2) The air dose to areas at or beyond the site boundary from noble gases released from the plant in gaseous effluent shall be limited:
 - (a) During any calendar quarter, to less than or equal to 5 mrad from gamma radiation, and less than or equal to 10 mrad from beta radiation; and,
 - (b) During any calendar year, to less than or equal to 10 mrad from gamma radiation and less than or equal to 20 mrad from beta radiation.
- b. Tritium, Iodines and Particulates, Half Lives > 8 days:
 - (1) The dose to a member of the public at or beyond the site boundary from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days released from the plant in gaseous effluent shall be limited:
 - (a) During any calendar quarter to less than or equal to 7.5 mrem to any organ; and,
 - (b) During any calendar year to less than or equal to 15 mrem to any organ.
 - (c) Less than 0.1% of the limits of Specification 3.4.1.c.1.a and 3.4.1.c.1.b as a result of burning contaminated oil.
 - (2) The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluents shall be limited as follows:
 - (a) Less than or equal to 1500 mrem/year to any organ from Iodine-131, Iodine-133, Tritium and for radioactive materials in particulate form with half-lives greater than 8 days (inhalation pathway only).

SUPPLEMENTAL INFORMATION (continued)

c. Liquid Effluents:

- (1) The concentration of radioactive materials released to the unrestricted areas shall not exceed ten times the values specified in 10 CFR 20.1001-20.2402, Appendix B, Table 2, column 2. For dissolved or entrained noble gases the concentration shall be limited to 2.00E-04 µCi/ml.
- (2) The dose to a member of the public from radioactive materials released from the plant in liquid effluents to unrestricted areas shall be limited as follows:
 - (a) During any calendar quarter, limited to less than or equal to 1.5 mrem to the whole body and to less than or equal to 5 mrem to any organ; and,
 - (b) During any calendar year, limited to less than or equal to 3 mrem to the whole body and to less than or equal to 10 mrem to any organ.

2. 10X Effluent Concentrations

a.	Fission and activation gases:	(None specified)					
b.	Iodines:	(None specified)					
c.	Particulates, half-lives >8 days:	(None specified)					
d.	Liquid effluents:	Quarter 1	Quarter 2	Quarter 3	Quarter 4		
	(1) Fission and activation products (mixture EC) (μCi/ml)	None	None	None	None		
	(2) Tritium (µCi/ml)	1.00E-02	1.00E-02	1.00E-02	1.00E-02		
	(3) Dissolved and entrained gases (µCi/ml)	2.00E-04	2.00E-04	2.00E-04	2.00E-04		

SUPPLEMENTAL INFORMATION (continued)

3. <u>Average Energy</u> (None specified)

4. Measurements and Approximations of Total Radioactivity

- a. Fission and Activation Gases: Continuous monitor on each release path calibrated to a marinelli grab sample analyzed by gamma spectroscopy; bubbler grab sample analyzed for Tritium.
- b. Iodines: Gamma spectral analysis of charcoal cartridge and particulate filter on each release path.
- c. Particulates: Gamma spectral analysis of each particulate filter and charcoal cartridge for each release path. A four week per quarter composite of particulate filters for each release path for Strontium-89 and Strontium-90. One week per month particulate filter for each release path for gross alpha.
- d. Liquid Effluents: Gamma spectral analysis of each batch discharged, except composite analysis for Strontium-89, Strontium-90, Iron-55, Tritium, and Alpha.
- e. Solid Waste: Gamma spectral analysis of a representative sample of each waste shipment. Scaling factors established from off-site composite sample analyses to estimate concentration of non-gamma emitters. Low activity trash shipments curie content is estimated by dose rate measurement and application of appropriate scaling factors.
- f. Error Estimation Method: Overall error for sampling and analysis estimated by combining individual errors using error propagation methods. This process is composed of determinate and undeterminate errors.

Determinate - Pump flowrates, volume measurements and analysis collection yields Undeterminate - Random counting error estimated using accepted statistical calculations

SUPPLEMENTAL INFORMATION (continued)

5. <u>Batch Releases</u>

a.	<u>Liquid: Canal</u>	Quarter 1	Quarter 2	Quarter 3	<u>Quarter 4</u>	
	(1) Number of batch	releases:	9.00E+00	1.30E+01	2.90E+01	1.00E+01
	(2) Total time period release: (min)	l for batch	5.52E+02	3.10E+02	8.37E+02	1.06E+02
	(3) Maximum time p batch release: (m	eriod for in)	4.23E+02	7.30E+01	1.28E+02	7.30E+01
	(4) Average time per batch release: (m	iod for in)	6.13E+01	2.38E+01	2.89E+01	1.06E+01
	(5) Minimum time per batch release: (m	eriod for in)	1.00E+00	1.00E+00	1.00E+00	1.00E+00
	(6) Total Activity Re	eleased (Ci)	0.00E+00	2.72E-06	6.76E-04	2.49E-06
	(7) Total Volume Re	eleased (liters)	2.09E+05	2.81E+08	3.42E+08	1.19E+08
b.	Liquid: Non-Canal		Quarter 1	Quarter 2	Quarter 3	Quarter 4
	(1) Number of batch	releases:	9.00E+00	1.00E+01	1.30E+01	8.00E+00
	()					
	(2) Total time period release: (min)	l for batch	5.52E+02	1.03E+02	2.77E+02	3.20E+01
	(2) Total time period release: (min)(3) Maximum time p batch release: (min)	l for batch eriod for in)	5.52E+02 2.38E+02	1.03E+02 2.22E+01	2.77E+02 4.50E+01	3.20E+01 7.80E+00
	 (2) Total time period release: (min) (3) Maximum time p batch release: (min) (4) Average time per batch release: (min) 	l for batch eriod for in) riod for in)	5.52E+02 2.38E+02 1.19E+02	1.03E+02 2.22E+01 5.88E+00	2.77E+02 4.50E+01 1.06E+01	3.20E+01 7.80E+00 2.27E+00
	 (2) Total time period release: (min) (3) Maximum time p batch release: (m (4) Average time per batch release: (m (5) Minimum time per batch release: (m 	l for batch eriod for in) tiod for in) eriod for in)	5.52E+02 2.38E+02 1.19E+02 1.00E+00	1.03E+02 2.22E+01 5.88E+00 1.00E+00	2.77E+02 4.50E+01 1.06E+01 1.20E+00	3.20E+01 7.80E+00 2.27E+00 1.00E+00
	 (2) Total time period release: (min) (3) Maximum time p batch release: (m (4) Average time per batch release: (m (5) Minimum time per batch release: (m (6) Total Activity Re 	l for batch eriod for in) riod for in) eriod for in) eleased (Ci)	5.52E+02 2.38E+02 1.19E+02 1.00E+00 3.79E-03	1.03E+02 2.22E+01 5.88E+00 1.00E+00 1.76E-04	2.77E+02 4.50E+01 1.06E+01 1.20E+00 3.50E-04	3.20E+01 7.80E+00 2.27E+00 1.00E+00 7.97E-05

c. Gaseous

There were no gaseous batch releases for this report period.

SUPPLEMENTAL INFORMATION (continued)

6. <u>Continuous Releases</u>

a.	Liquid: Non-Canal	Quarter 1	Quarter 2	Quarter 3	Quarter 4
	(1) Number of releases:	1.30E+01	1.20E+01	1.30E+01	1.30E+01
	(2) Total Activity Released (Ci)	7.22E-03	7.10E-03	9.06E-03	8.19E-03
	(3) Total Volume Released (liters)	5.70E+07	5.46E+07	4.61E+07	4.02E+07

b.	Liquid: Canal	Quarter 1	Quarter 2	Quarter 3	Quarter 4	
	(1) Number of releases:	0	0	0	0	
	(2) Total Activity Released (Ci)	N/A	N/	Ά	NA	NA

TABLE 1AGASEOUS EFFLUENTS - SUMMATION OF ALL RELEASES

			<u>UNIT</u>	<u>QTR 1</u>	<u>QTR 2</u>	<u>QTR 3</u>	<u>QTR 4</u>	EST TOTAL ERROR %
A.	FI	SSION AND ACTIVATION GASES						
	1.	Total Release	Ci	7.86E+01	5.22E+01	2.12E+01	1.22E+01	≤2.50E+01
	2.	Average release rate for period	µCi/sec	1.01E+01	6.64E+00	2.67E+00	1.54E+00	
	3.	Applicable ODCM Limit	%	*	*	*	*	
B.	IO	DINE-131						
	1.	Total Iodine-131	Ci	9.30E-05	1.44E-04	9.11E-05	6.84E-05	≤2.50E+01
	2.	Average release rate for period	µCi/sec	1.20E-05	1.83E-05	1.15E-05	8.60E-06	
	3.	Applicable ODCM Limit	%	*	*	*	*	
C.	PA	RTICULATES						
	1.	Particulates with half-lives >8 days	Ci	2.61E-06	2.34E-06	1.53E-04	6.23E-05	≤3.60E+01
	2.	Average release rate for period	µCi/sec	3.35E-07	2.98E-09	1.92E-05	7.84E-06	
	3.	Applicable ODCM Limit	. %	*	*	*	*	
	4.	Gross alpha radioactivity	Ci	3.06E-07	5.36E-07	2.38E-07	1.46E-07	≤2.50E+01
D.	TR	RITIUM						
	1.	Total Release	Ci	6.49E+00	5.15E+00	2.06E+00	3.36E+00	≤2.50E+01
	2.	Average release rate for period	µCi/sec	8.35E-01	6.54E-01	2.59E-01	4.22E-01	
	3.	Applicable ODCM Limit	%	*	*	*	*	
E.	CA	ARBON-14 (See attachment 8)						
*F.	PE	ERCENT OF APPLICABLE ODCM L	IMITS					
	FI	SSION AND ACTIVATION GASES	<u>UNIT</u>	<u>QTR 1</u>	<u>QTR 2</u>	<u>QTR 3</u>	QTR 4	
	1.	Quarterly gamma air dose limit	%	4.31E-02	3.04E-02	1.44E-02	7.48E-03	
	2.	Quarterly beta air dose limit	%	5.80E-03	5.99E-03	3.59E-03	6.67E-04	
	3.	Yearly gamma air dose limit	%	2.16E-02	1.52E-02	7.20E-03	3.74E-03	
	4.	Yearly beta air dose limit	%	1.45E-03	1.50E-03	8.98E-04	1.67E-04	
	5.	Whole body dose rate limit	%	3.84E-02	9.88E-03	1.35E-02	1.33E-03	
	6.	Skin dose rate limit	%	7.78E-03	2.13E-03	2.73E-03	2.74E-04	
	HA	ALOGENS, TRITIUM AND PARTICI	JLATES W	ITH HALF-L	IVES >8 DAY	ΎS		

7.	Quarterly dose limit (organ)	%	1.91E-02	2.69E-02	1.74E-02	1.38E-02
8.	Yearly dose limit (organ)	%	9.55E-03	1.35E-02	8.71E-03	6.92E-03
9.	Organ dose rate limit	%	2.51E-05	2.56E-05	1.57E-05	2.82E-05

TABLE 1BGASEOUS EFFLUENTS - ELEVATED RELEASE

CONTINUOUS MODE

NUCLIDES RELEASED

1.	Fission Gases	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
	Argon-41	Ci	1.95E+01	3.75E+00	6.43E+00	8.59E+00
	Krypton-85m	Ci	9.65E-01	1.62E+00	2.54E+00	1.61E+00
	Krypton-87	Ci	5.18E+00	5.63E+00	4.50E-01	ND
	Krypton-88	Ci	2.85E+00	3.52E+00	1.87E+00	1.37E+00
	Xenon-133	Ci	7.09E-01	3.91E-01	2.64E+00	6.04E-01
	Xenon-135	Ci	7.18E+00	6.67E+00	3.70E-01	2.22E-02
	Xenon-135m	Ci	1.10E+01	6.93E+00	8.53E-01	ND
	Xenon-137	Ci	8.01E-01	ND	ND	ND
	Xenon-138	Ci	3.04E+01	2.15E+01	3.46E+00	ND
	TOTAL	Ci	7.86E+01	5.00E+011	1.86E+01	1.22E+01
2.	<u>Iodines</u>					
	Iodine-131	Ci	1.65E-05	3.15E-05	1.60E-05	1.18E-05
	Iodine-132	Ci	ND	3.11E-05	ND	ND
	Iodine-133	Ci	4.97E-05	8.92E-05	5.97E-05	3.78E-05
	Iodine-135	Ci	ND	6.56E-05	7.87E-06	ND
	TOTAL	Ci	6.62E-05	2.17E-04	8.36E-05	4.96E-05
3.	Particulates					
	Cobalt-60	Ci	ND	ND	6.12E-07	ND
	Cesium-137	Ci	2.61E-06	ND	ND	ND
	Manganese-54	Ci	ND	ND	6.92E-07	ND
	Strontium-89 Zinc-65	Ci	ND ND	ND ND	8.88E-07 5.64E-07	5.52E-07 ND
	TOTAL	Ci	2.61E-06	ND	2.76E-06	5.52E-07
4.	<u>Tritium</u>					
	Hydrogen-3	Ci	4.32E-01	2.39E-01	1.88E-01	2.41E-01

Note: There were no batch releases for this report period.

TABLE 1CGASEOUS EFFLUENTS - GROUND LEVEL RELEASES

CONTINUOUS MODE

NUCLIDES RELEASED

1.	Fission Gases	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
	Xe-138	Ci	ND	2.15E+00	2.64E+00	ND
	TOTAL	Ci	ND	2.15E+00	2.65E+00	ND
2.	<u>Iodines</u>					
	Iodine-131	Ci	7.64E-05	1.12E-04	7.51E-05	5.66E-05
	Iodine-133	Ci	5.48E-04	8.70E-04	4.85E-04	5.51E-04
	TOTAL	Ci	6.24E-04	9.82E-04	5.60E-04	6.08E-4
3.	Particulates					
	Silver-110M	Ci	ND	2.34E-08	ND	ND
	Cobalt-58	Ci	ND	ND	ND	ND
	Cobalt-60	Ci	ND	ND	8.66E-06	ND
	Manganese-54	Ci	ND	ND	1.15E-05	ND
	Selenium-75	Ci	ND	ND	ND	ND
	Strontium-89	Ci	ND	ND	4.05E-05	6.16E-05
	Zinc-65	Ci	ND	ND	8.59E-05	2.19E-07
	TOTAL	Ci	ND	2.34E-08	1.47E-04	6.18E-05
4.	<u>Tritium</u>					
	Hydrogen-3	Ci	6.06E+00	4.91E+00	1.87E+00	3.12E+00

TABLE 1CGASEOUS EFFLUENTS - GROUND LEVEL RELEASES

BATCH MODE

NUCLIDES RELEASED

1.	Fission Gases	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
	Xenon-133 Xenon-135	Ci Ci	ND ND	ND ND	ND ND	5.34E-03 3.27E-03
	TOTAL	Ci	ND ND	ND	ND	ND 8.61E-03
2.	<u>Iodines</u>					
	TOTAL	Ci	ND	ND	ND	ND
3.	Particulates					
	Cobalt-60	Ci	ND	ND	3.45E-06	ND
	TOTAL	Ci	ND	ND	3.45E-06	ND
4.	<u>Tritium</u>					
	Hydrogen-3	Ci	ND	ND	ND	ND

9

TABLE 2A LIQUID EFFLUENTS - SUMMATION OF ALL RELEASES

			<u>UNIT</u>	<u>QTR 1</u>	<u>QTR 2</u>	<u>QTR 3</u>	<u>QTR 4</u>	EST TOTAL ERROR %
A.	FIS	SSION AND ACTIVATION PRODU	CTS					
NΔ	1.	Total Release (not including tritium, gases and alpha)	Ci	ND	ND]	ND	ND
1174	2.	Average diluted concentration during period	µCi/ml	ND	ND	ND	ND	
	3.	Applicable ODCM Limit	%	NA	NA	NA	NA	A
B.	TR	ITIUM						
	1. 2.	Total Release Average diluted concentration	Ci	1.10E-02	7.28E-03	1.01E-02	8.27E-03	≤2.50E+01
		during period (Note 1)	µCi/ml	1.86E-06	1.32E-06	1.96E-06	2.05E-06	
	3.	Applicable ODCM Limit	%	*	*	*	*	
C.	DIS	SSOLVED AND ENTRAINED GASE	ES					
	1. 2.	Total Release Average diluted concentration	Ci	ND	ND	ND	ND	NA
		during period	$\mu Ci/ml$	ND	ND	ND	ND	
	3.	Applicable ODCM Limit	%		NA	NA	NA	NA
D.	GR	COSS ALPHA RADIOACTIVITY						
	1.	Total Release	Ci	ND	ND	ND	ND	NA
E.	VO (PF	DLUME OF WASTE RELEASED RIOR TO DILUTION)	liters	5.91E+06	5.50E+06	4.81E+06	4.03E+06	
F.	VO US	DLUME OF DILUTION WATER ED DURING PERIOD	liters	0.00E+00	2.81E+08	3.42E+08	1.19E+08	
*G.	PE	RCENT OF APPLICABLE ODCM I	LIMITS					
	1.	Quarterly Whole Body Dose	%	4.13E-04	7.06E-04	4.35E-04	7.09E-04	
	2.	Quarterly Organ Dose	%	1.24E-04	2.12E-04	1.31E-04	2.13E-04	
	3.	Annual Whole Body Dose	%	2.06E-04	3.53E-04	2.18E-04	3.55E-04	
	4.	Annual Organ Dose	%	6.19E-05	1.06E-04	6.53E-05	1.06E-04	

Note 1: Concentration includes summation from diluted and undiluted values from Canal and Non-Canal releases (Table 2B).

TABLE 2BLIQUID EFFLUENTS CANAL

BATCH MODE

NU	JCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4	
1.	Fission and Activation Product	<u>s</u>					
	ND	Ci	ND	ND	ND	ND	
2.	<u>Tritium</u>						
	Hydrogen-3	Ci	ND		2.72E-06	6.76E-04 2.49E	3-06
3.	Dissolved and Entrained Gases	<u>.</u>					
	ND	Ci	ND	ND	ND	ND	

TABLE 2B LIQUID EFFLUENTS CANAL

CONTINUOUS MODE

NU	JCLIDES RELEASED	<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
1.	Fission and Activation Produc	<u>ts</u>				
	ND	Ci	ND	ND	ND	ND
2.	<u>Tritium</u>					
	Hydrogen-3	Ci	ND	ND	ND	ND
3.	Dissolved and Entrained Gase	<u>s</u>				
	ND	Ci	ND	ND	ND	ND

TABLE 2B (SUPPLEMENT)LIQUID EFFLUENTS NON-CANAL

CONTINUOUS MODE

NUCLIDES RELEASED		<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4	
1.	Fission and Activation Pro	ducts					
	ND	Ci	ND	ND	ND	ND	
2.	<u>Tritium</u>						
	Hydrogen-3	Ci	7.22E-03	7.10E-03	9.06E-03	8.19E-03	
3.	Dissolved and Entrained G	<u>ases</u>					
	ND	Ci	ND	ND	ND	ND	

TABLE 2B (SUPPLEMENT)LIQUID EFFLUENTS NON-CANAL

BATCH MODE

NUCLIDES RELEASED		<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4	
1.	Fission and Activation Prod	lucts					
	ND	Ci	ND	ND	ND	ND	
2.	<u>Tritium</u>						
	Hydrogen-3	Ci	3.79E-03	1.76E-04	3.50E-04	7.97E-05	
3.	Dissolved and Entrained Ga	<u>ases</u>					
	ND	Ci	ND	ND	ND	ND	

TABLE 2B (CONTINUED)ABNORMAL RELEASELIQUID EFFLUENTS CANAL

CONTINUOUS MODE

NUCLIDES RELEASED		<u>UNIT</u>	QUARTER 1	QUARTER 2	QUARTER 3	QUARTER 4
1.	Fission and Activation Product	<u>ucts</u>				
	ND	Ci	ND	ND	ND	ND
2.	<u>Tritium</u>					
	ND	Ci	ND	ND	ND	ND
3.	Dissolved and Entrained Ga	<u>ses</u>				
	ND	Ci	ND	ND	ND	ND

TABLE 3ASOLID WASTE AND IRRADIATED FUEL SHIPMENTS

A. SOLID WASTE SHIPPED OFFSITE FOR BURIAL OR DISPOSAL (NOT IRRADIATED FUEL)

						ESI. IUIAL
1.	<u>Type of Waste</u>	UNIT	CLASS A	CLASS B	CLASS C	ERROR %
	a. Spent resins, filter sludges,	m^3	0.00E + 00	0.00E + 00	0.00E+00	0.00E+00
	evaporator bottoms, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	b. Dry compressible waste,	m^3	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	contaminated equipment, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	c. Irradiated components,	m^3	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	control rods, etc.	Ci	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	d. Other: Dry compressible	m^3	1.77E+03	1.13E+01	0.00E+00	2.50E+01
	waste, contaminated equipment, spent resins for volume reduction.	Ci	1.57E+01	4.36E+02	0.00E+00	2.50E+01

2. Estimate of Major Nuclide Composition (by type of waste)

a. Spent resins, filter sludges, evaporator bottoms, etc.

None

b. Dry compressible waste, contaminated equipment, etc.

None

c. Irradiated components, control rods, etc.

None

d. Other: Dry compressible waste, contaminated equipment, spent resins contaminated oil, glycol and water for volume reduction.

Isotope	Percent	Curies	Isotope	Percent	<u>Curies</u>
H-3	1.52E-01	2.38e-02 E	La-140	4.10E-02	6.48E-03 E
C-14	5.66E-01	8.85E-02 E	Ce-141	2.30E-02	3.59E-03 E
Cr-51	4.22E-01	6.60E-02 E	Mn-54	7.79E+00	1.22E+00 E
Fe-55	3.01E+01	4.71E+00 E	Fe-59	2.69E-01	4.20E-02 E
Co-58	2.99E-01	4.67E-02 E	Co-60	1.87E+01	2.93E+00 E
Ni-63	4.93E+00	7.72E-01 E	Zn-65	3.14E+01	4.87E+00 E
Sb-124	3.50E-02	5.51E-03 E	I-131	2.00E-02	3.13E-03 E
Cs-134	1.14E-01	2.20E-02 E	Cs-137	5.30E+00	8.28E-01 E
Ba-140	6.40E-02	1.01E-02 E			

(E-Estimated M-Measured)

Percentage of nuclides and total activities are based on a combination of direct measurements and scaling for non-gamma emitting nuclides.

TABLE 3A (continued) SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

3. Solid Waste Disposition

No. of Shipments	Mode of Transportation	Destination
37	Truck	*Energy Solutions Oak Ridge, TN
27	Truck	*Energy Solutions Kingston, TN

* Volume Reduction Facility

B. IRRADIATED FUEL SHIPMENTS (Disposition)

No. of Shipments	Mode of Transportation	Destination
None		

TABLE 3B SOLID WASTE AND IRRADIATED FUEL SHIPMENTS

A. NRC CLASS A

B.

C.

SOURCE OF <u>WASTE</u>	PROCESSING <u>EMPLOYED</u>	CONTAINER <u>VOLUME</u>	TYPE OF <u>CONTAINER</u>	NUMBER OF <u>CONTAINERS</u>
Dry compressible Waste (DAW), Contaminated Equipment, etc.	Non-compacted	1280 ft^3	STC	38
Dry compressible Waste (DAW), Contaminated Equipment, etc.	Non-compacted	96 ft^3	STC	164
Dry compressible Waste (DAW), Contaminated Equipment, etc.	Non-compacted	1033 ft^3	STC	7
Dry compressible Waste (DAW), Contaminated Equipment, etc.	Non-compacted	525 ft^3	STC	2
Spent Resins, Filter Sludges, evaporator Bottoms, etc.	Air Drying Non-compacted	205.8 ft^3	HIC	39
NRC CLASS B				
SOURCE OF <u>WASTE</u>	PROCESSING EMPLOYED	CONTAINER <u>VOLUME</u>	TYPE OF <u>CONTAINER</u>	NUMBER OF <u>CONTAINERS</u>
	None			
NRC CLASS C				
SOURCE OF <u>WASTE</u>	PROCESSING <u>EMPLOYED</u>	CONTAINER <u>VOLUME</u>	TYPE OF <u>CONTAINER</u>	NUMBER OF <u>CONTAINERS</u>
	None			

HIC- High Integrity Container

STC-Strong Tight Container

ATTACHMENT NO. 1

CHANGES TO THE OFFSITE DOSE CALCULATION MANUAL (ODCM)

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 6.2.3, changes made to the Offsite Dose Calculation Manual (ODCM) during the reporting period shall be included in the Annual Radioactive Effluent Release Report.

There were no changes made to the ODCM during this reporting period.

ATTACHMENT NO. 2

SUMMARY OF CHANGES TO THE PROCESS CONTROL PROGRAM

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 6.2.3, changes made to the Process Control Program (PCP) during the reporting period shall be included in the Annual Radioactive Effluent Release Report.

There were no changes to the Process Control Program.

ATTACHMENT NO. 3

SUMMARY OF CHANGES TO THE ENVIRONMENTAL MONITORING AND DOSE CALCULATION LOCATIONS

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1, Section 6.2.3 a listing of new locations for dose calculation and/or environmental monitoring identified by the land use census shall be included in the Annual Radioactive Effluent Release Report.

There were no new locations identified in the land use census.

During the reporting period, no changes in Dose Calculation Receptor Locations and/or the Environmental Monitoring were required based on the results of the land use census.

ATTACHMENT NO. 4

DEVIATIONS FROM THE REQUIRED ENVIRONMENTAL SAMPLING SCHEDULE

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1, Section 6.2.7, the cause for the unavailability of any environmental samples required during the report period shall be included in the Annual Radioactive Effluent Release Report.

The following reports samples that were a deviation from the requirements of ODCM Part 1, Table 5.1-1. ODCM Part Section 5.1.1.c.1 allows for deviations from the program due to hazardous conditions, seasonal unavailability, theft, uncooperative residents, or to a malfunction of automatic sampling equipment.

A. ODCM Program Deviations

The following are deviations from the program specified by the ODCM:

- 02/04/2014 Air Station R-3 Offsite, volumetric flow rate exceeded the acceptance criteria of 108 132 cubic feet per hour. Flow rate was found at 96 cubic feet per hour.
- 02/26/2014 Air Station R-1 Offsite , volumetric flow rate exceeded the acceptance criteria of 108 132 cubic feet per hour. Flow rate was found at 134 cubic feet per hour.
- 07/15/2014 Air Station R-2 Offsite, lost power for approximately 5 hours during the sample period.

B. <u>Air Sampling Station Operability Assessment</u>

The ODCM required air sampling program consists of 5 individual sampling locations. The collective operable time period for the air monitoring stations was 43,825 hours out of a possible 43830 hours. The air sampling availability factor for the report period was 99.9%. Air sampling equipment found inoperable was returned to service. Identification of locations for obtaining replacement samples was not required.

ATTACHMENT NO. 5

ANNUAL SUMMARY OF HOURLY METEOROLOGICAL DATA

The James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1, Radiological Controls (REC) Section 6.2 and 6.2.2 states in part: The Annual Radioactive Effluent Release Report submitted prior to May 1 of each year may include an annual summary of meteorological data collected over the previous year. If the meteorological data is not included, the licensee shall retain it on file and provide it to the U.S. Nuclear Regulatory Commission upon request.

In accordance with the aforementioned ODCM requirement, meteorological data is not included in this report. It is retained on file and is available upon request.

ATTACHMENT NO. 6

MAJOR MODIFICATIONS TO RADIOACTIVE LIQUID, GASEOUS AND SOLID WASTE TREATMENT SYSTEMS

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 7.0, Major Modifications to Radioactive Waste Treatment Systems (liquid, gaseous and solid) shall be reported in the Annual Radioactive Effluent Release Report for the period in which the modification is completed and made operational.

There were no major modifications to any liquid, gaseous, or solid radioactive waste treatment systems.

ATTACHMENT NO. 7

ONSITE GROUNDWATER MONITORING

In response to the Nuclear Energy Institute (NEI) Groundwater Protection Initiative, JAF instituted a groundwater monitoring program in 2007. Five monitoring wells were installed during the fourth quarter of 2007. The first samples were collected in November 2007. Starting in March 2010, 16 additional monitoring wells were drilled in the area of the Reactor Building and nearby SSCs. In August 2013, 3 additional wells and 2 piezometers were installed on site.

All samples collected were analyzed for tritium and gamma emitting radionuclides. The detection limits and results are reported in the following tables. Analysis results of tritium ranged from non-detectable, a minimum positive indication of 446 pCi/l, and a maximum concentration of 5968 pCi/l for a CST-B sample from 3/19/14. Such levels are below the Reporting Level of the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1, Table 5.1-2, for tritium. The Reporting Level for tritium is 30,000 pCi/l. No drinking water sources are affected by this tritium. All of the effected wells are onsite. As such, there is no potential to influence any off-site drinking well. No drinking water pathway exists at the James A. FitzPatrick site under normal operating conditions due to the direction and distance of the nearest water intake (Oswego, 8.5 miles west of the JAF discharge).

In conclusion, the only radionuclide detected in groundwater during the 2014 monitoring effort that is attributable to James A. FitzPatrick operations is tritium, and all concentrations were below any reporting criteria.

ATTACHMENT NO. 7 (continued)

ONSITE GROUNDWATER MONITORING

A) Gamma Isotopic Monitoring

For 2014, the 24 monitoring wells were sampled quarterly, providing enough water was present, and analyzed below the required lower limits of detection in accordance with the Offsite Dose Calculation Manual (ODCM) Part 1, Table 5.1-3.

Radionuclide	LLD Value (pCi/l)
Manganese-54	15
Cobalt-58	15
Iron-59	30
Cobalt-60	15
Zinc-65	30

	LLD Value
Radionuclide	(pCi/l)
Zirconium/Niobium-95	15
Iodine-131	15
Cesium-134	15
Cesium-137	18
Barium/Lanthanum-140	15

There were no plant related nuclides detected in the samples. Gross Beta and Hard to Detect nuclide analysis not required.

ATTACHMENT NO. 7 (continued)

ONSITE GROUNDWATER MONITORING

B) Tritium Summary

Well Name	# Samples in 2014	# Positive Samples in 2014	Minimum Positive Concentration	Maximum Positive Concentration
MW-1A	4	0		
MW-1B	3	0		
MW-2A	4	0		
MW-2B	4	0		
MW-3A	4	0		
MW-3B	4	1	446	446
MW-4A	4	0		
MW-4B	3	0		
MW-5	4	0		
MW-6	4	0		
MW-7	4	0		
MW-8	4	0		
MW-9	4	0		
MW-10A	4	0		
MW-10B	4	0		
MW-13	4	0		
MW-14	4	0		
MW-15	4	0		
MW-16	4	0		
MW-19	4	0		
MW-20	3	0		
MW-21	4	0		
CST-A	2	0		
CST-B	4	4	1880	5968

Note 1: All results are in pCi/L.

Note 2: A total of 91 samples were analyzed for H-3 in 2014 with 5 positive results.

ATTACHMENT NO. 8

GASEOUS EFFLUENTS – CARBON-14

a)	Date:	January 01, 2014 – December 31, 2014				
b)	Location:	Elevated Release – Main Stack				
c)	Duration:	365 Days				
d)	Flow rate:	N/A				
e)	Volume Released:	N/A				
f)	Nuclides Released:	Carbon-14				
g)	Curies Released ⁽¹⁾ :	<u>UNIT</u>	<u>QTR 1</u>	<u>QTR 2</u>	<u>QTR 3</u>	<u>QTR 4</u>
0.27	E 100	Ci	2.50E+00	2.08E+00	1.34E+00	
2.37E+00		µCi/sec	3.21E-01	2.65E-01	1.69E-01	2.98E-01
h)	Resultant Doses:	See Addendum 1—Assessment of Radiation Doses to the Public January-December 2014 Table 1E				
i)	Dose Calculations:	Doses were ca Calculation M	alculated in acc Ianual (ODCM	cordance with t) Section 4.4.1	he Offsite Dos	e

⁽¹⁾Curies released calculated using the methodology in EPRI Technical Report 1021106 **"Estimation of Carbon-14 in Nuclear Power Plant Gaseous Effluents".**

ATTACHMENT NO. 9

EVENTS LEADING TO CONDITIONS WHICH RESULTED IN EXCEEDING RADIOACTIVITY LIMITS.

In accordance with the James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls (REC) Section 6.2.9, the report shall contain the events leading to the conditions which resulted in exceeding the radioactivity limits for the specified outdoor radioactive radwaste tanks specified in the Technical Requirements Manual, TRM 3.7.E

The radioactivity limits for the specified outdoor radioactive radwaste tanks were not exceeded.

ADDENDUM 1

ASSESSMENT OF RADIATION DOSES TO THE PUBLIC JANUARY - DECEMBER 2014

1. INTRODUCTION

The James A. FitzPatrick Nuclear Power Plant Offsite Dose Calculation Manual (ODCM), Part 1 Radiological Controls, requires an assessment of the radiation doses to the likely most exposed member of the public due to radioactive liquid and gaseous effluents. This assessment of doses to the likely most exposed member of the public is based on accepted methodologies found in the Offsite Dose Calculation Manual (ODCM).

2. DOSE LIMITS

A. DOSE FROM LIQUID EFFLUENTS (ODCM, Part 1, REC 2.3)

Applicability

Applies to doses from radioactive material in liquid effluents.

Objective

To ensure that the dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The dose to a member of the public from radioactive materials released from the plant in liquid effluents to unrestricted areas shall be limited as follows:

- 1. During any calendar quarter, limited to less than or equal to 1.5 mrem to the whole body and to less than or equal to 5 mrem to any organ.
- 2. During any calendar year, limited to less than or equal to 3 mrem to the whole body and to less than or equal to 10 mrem to any organ.

B. GASEOUS DOSE RATES (ODCM, Part 1, REC 3.2)

Applicability

Applies to the radiation dose from radioactive material in gaseous effluents.

Objective

To ensure that the dose rates at or beyond the site boundary from gaseous effluents do not exceed the annual dose limits of 10 CFR 20, for unrestricted areas.

ADDENDUM 1 (continued)

Specifications

The dose rate at or beyond the site boundary due to radioactive materials released from the plant in gaseous effluents shall be limited as follows:

- 1. Less than or equal to 500 mrem/year to the whole body and less than or equal to 3000 mrem/year to the skin from noble gases; and,
- 2. Less than or equal to 1500 mrem/year to any organ from Iodine-131, Iodine-133, Tritium and for radioactive materials in particulate form with half-lives greater than 8 days (inhalation pathway only).
- C. AIR DOSE, NOBLE GASES (ODCM, Part 1, REC 3.3)

Applicability

Applies to the air dose due to noble gases in gaseous effluents.

Objective

To ensure that the noble gas dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The air dose to areas at or beyond the site boundary from noble gases released from the plant in gaseous effluents shall be limited:

- 1. During any calendar quarter, to less than or equal to 5 mrad from gamma radiation, and less than or equal to 10 mrad from beta radiation; and,
- 2. During any calendar year, to less than or equal to 10 mrad from gamma radiation and less than or equal to 20 mrad from beta radiation.

ADDENDUM 1 (continued)

D. DOSE DUE TO IODINE-131, IODINE-133, TRITIUM AND RADIONUCLIDES IN PARTICULATE FORM (ODCM, Part 1, REC 3.4)

Applicability

Applies to the cumulative dose from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days in gaseous effluents.

Objective

To ensure that the dose limitations of 10 CFR 50, Appendix I, are met.

Specifications

The dose to a member of the public at or beyond the site boundary from Iodine-131, Iodine-133, Tritium, and radionuclides in particulate form with half-lives greater than 8 days released from the plant in gaseous effluents shall be limited:

- 1. During any calendar quarter to less than or equal to 7.5 mrem to any organ; and,
- 2. During any calendar year to less than or equal to 15 mrem to any organ.

E. TOTAL DOSE FROM URANIUM FUEL CYCLE (ODCM, Part 1, REC 4.0)

Applicability

Applies to radiation dose from releases of radioactivity and radiation from uranium fuel cycle sources.

Objective

To ensure that the requirements of 40 CFR 190 are met.

Specifications

The dose or dose commitment to any member of the public, due to releases of radioactivity and radiation, from uranium fuel cycle sources shall be limited as follows:

- 1. Less than or equal to 25 mrem/year to the whole body; and,
- 2. Less than or equal to 25 mrem/year to any organ except the thyroid which shall be limited to less than or equal to 75 mrem/year.

ADDENDUM 1 (continued)

3. DOSE ASSESSMENT

A. <u>METHODOLOGY</u>

The assessment of radiation doses to the public due to radioactive liquid and gaseous effluents is performed in accordance with the ODCM. The ODCM is based on methodologies and models suggested by the "Guidance Manual For Preparation of Radiological Effluent Technical Specifications for Nuclear Power Plants" (NUREG-0133) and "Calculation of Annual Doses to Man from Routine Releases of Reactor Effluents for the purpose of Evaluating Compliance with 10CFR50, Appendix I" (Regulatory Guide 1.109).

B. ASSUMPTIONS

Dose calculations are performed using formulas and constants defined in the ODCM. Specific radioactive release activities used in the dose calculations are listed in the Annual Radioactive Effluent Release Report (1.21 Report) for the period of January 1, 2014 to December 31, 2014. Historical meteorological data was used to generate tables of average dispersion factors. Locations of interest were identified from the 2014 land use census. Dispersion factors and locations of interest used in performing the dose calculations are listed in Table 2.

C. ASSESSMENT RESULTS SUMMARY

The calculated doses to the public due to radioactive effluents are listed in Table 1. The calculated doses are small fractions of their respective dose limits.

4. 40 CFR 190 DOSE ASSESSMENT

A. <u>METHODOLOGY</u>

Evaluation to demonstrate compliance with the 40 CFR 190 dose limits must be performed when the doses calculated for 10 CFR 50 compliance exceed twice their respective limits. When additional dose assessment is required to demonstrate compliance with 40 CFR 190 it is performed in accordance with the ODCM.

B. <u>RESULTS SUMMARY</u>

The cumulative dose contribution from liquid and gaseous effluents for this report period were calculated and are listed in Table 1. The cumulative dose contribution from direct radiation from the reactor unit and from radwaste storage tanks is measured by environmental thermoluminescent dosimeters for the report period. This data is contained in the Annual Environmental Operating Report. The calculated doses from liquid and gaseous effluents are less than twice their respective 10 CFR 50 limits; therefore, additional calculations are not necessary to demonstrate compliance with 40 CFR 190 dose limits.

ADDENDUM 1 (continued)

	ANNUAL	DOSE ASS		2014		
A. LIQUIDS						
<u>QUARTER</u>	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	ANNUAL	
	(a)	(a)	(a)	(a)	(a)	
Organ (mrem)	6.19E-06	1.06E-05	6.53E-06	1.06E-05	3.40E-05	
% of Limit	1.24E-04	2.12E-04	1.31E-04	2.13E-04	3.40E-04	
	(b)	(b)	(b)	(b)	(b)	
Whole Body (mrem)	6.19E-06	1.06E-05	6.53E-06	1.06E-05	3.40E-05	
% of Limit	4.13E-04	7.06E-04	4.35E-04	7.09E-04	1.13E-03	

TABLE 1 ANNUAL DOSE ASSESSMENT 2014

(a) Dose to the Child Liver primarily by the potable water pathway.

(b) Dose to the Child Whole Body primarily by the potable water pathway.

ADDENDUM 1 (continued)

TABLE 1 (cont)ANNUAL DOSE ASSESSMENT 2014

B. NOBLE GASES

QUARTER	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>ANNUAL</u>
Total Body (mrem/yr)	1.92E-01	4.94E-02	6.73E-02	6.65E-03	1.92E-01
% of Limit	3.84E-02	9.88E-03	1.35E-02	1.33E-03	3.84E-02
Skin (mrem/yr)	2.34E-01	6.38E-02	8.18E-02	8.21E-03	2.34E-01
% of Limit	7.78E-03	2.13E-03	2.73E-03	2.74E-04	7.78E-03
Gamma (mrad)	2.16E-03	1.52E-03	7.20E-04	3.74E-04	4.77E-03
% of Limit	4.31E-02	3.04E-02	1.44E-02	7.48E-03	4.77E-02
Beta (mrad)	2.90E-04	3.00E-04	1.80E-04	3.34E-05	8.02E-04
% of Limit	5.80E-03	5.99E-03	3.59E-03	6.67E-04	4.01E-03

C. IODINES AND PARTICULATES

<u>QUARTER</u>	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>ANNUAL</u>
	(a)	(a)	(a)	(a)	(a)
Organ (mrem)	1.43E-03	2.02E-03	1.31E-03	1.04E-03	5.78E-03
% of Limit	1.91E-02	2.69E-02	1.74E-02	1.38E-02	7.71E-02
	(a)	(a)	(a)	(a)	(a)
Organ Dose Rate	3.77E-04	3.84E-04	2.35E-04	4.22E-04	4.22E-04
% of Limit	2.51E-05	2.56E-05	1.57E-05	2.82E-05	2.82E-05

(a) Dose to the Child Thyroid primarily by the vegetation pathway.

ADDENDUM 1 (continued)

TABLE 1 (cont)ANNUAL DOSE ASSESSMENT 2014

D. CARBON 14					
<u>QUARTER</u>	<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>	<u>ANNUAL</u>
	(a)	(a)	(a)	(a)	(a)
Organ (mrem)	7.99E-03	6.63E-03	4.26E-03	7.55E-03	2.64E-02
% of Limit	1.06E-01	8.84E-02	5.68E-02	1.01E-01	1.76E-01
					(a)
Organ Dose Rate	NA	NA	NA	NA	3.20E-02
% of Limit	NA	NA	NA	NA	1.07E-03

(a) Dose to the Child Bone primarily by the vegetation pathway.

ADDENDUM 1 (continued)

TABLE 2 METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

	DECEDTOD	GEOGRAPHIC		ATMOS	PHERIC**
	RECEPTOR	LUCATION		DISPERSIO	NFACIOR
A.	IODINE &	DISTANCE/	RELEASI	E X/Q	D/Q
	PARTICULATES	DIRECTION	POINT	(sec/m^3)	$(1/m^2)$
1.	Garden	0.90 mi @ 83°E	ST	2.83E-08*	1.75E-09
	Grazing Season	0.90 mi @ 83°E	RX	2.02E-07*	5.01E-09
	Cary	0.90 mi @ 83°E	TB	1.83E-07*	4.80E-09
	Location No. 78	0.90 mi @ 83°E	RF	2.02E-07*	5.01E-09
		0.90 mi @ 83°E	RW	3.21E-07*	5.76E-09
2.	Meat	1.18 mi @ 127°SE	ST	1.72E-08*	6.80E-10
	Grazing Season	1.18 mi @ 127°SE	RX	5.36E-08*	1.30E-09
	Parkhurst	1.18 mi @ 127°SE	TB	5.14E-08*	1.27E-09
	Location No. 26	1.18 mi @ 127°SE	RF	5.36E-08*	1.30E-09
		1.18 mi @ 127°SE	RW	9.12E-08*	1.46E-09
3.	Cow	2.50 mi @ 139°SE	ST	1.67E-08*	2.65E-10
	Grazing Season	2.50 mi @ 139°SE	RX	2.76E-08*	4.14E-10
	France	2.50 mi @ 139°SE	TB	2.71E-08*	4.07E-10
	Location No. 10	2.50 mi @ 139°SE	RF	2.76E-08*	4.14E-10
		2.50 mi @ 139°SE	RW	4.15E-08*	4.36E-10
4.	Goat (D/Q)	3.62 mi @ 113°ESE	ST	NA	2.28E-10
	Grazing Season	3.62 mi @ 113°ESE	RX	NA	3.40E-10
	Showers	3.62 mi @ 113°ESE	TB	NA	3.33E-10
	Location No. 71	3.62 mi @ 113°ESE	RF	NA	3.40E-10
		3.62 mi @ 113°ESE	RW	NA	3.49E-10
5.	Goat (X/Q)	2.64 mi @ 152°SSE	ST	1.94E-08*	NA
	Grazing Season	2.64 mi @ 152°SSE	RX	2.58E-08*	NA
	Nickolas	2.64 mi @ 152°SSE	TB	2.57E-08*	NA
	Location No. 61	2.64 mi @ 152°SSE	RF	2.58E-08*	NA
		2.64 mi @ 152°SSE	RW	3.59E-08*	NA

ADDENDUM 1 (continued)

TABLE 2 METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

	RECEPTOR	GEOGRAPHIC LOCATION	1	ATMOSI DISPERSION	PHERIC** N FACTOR
A.	IODINE & PARTICULATES	DISTANCE/ DIRECTION	RELEASE POINT	X/Q (sec/m3)	D/Q (l/m2)
6.	Resident Annual Average				
	a. Inhalation ⁽²⁾	1.55 mi @ 90°E ⁽¹⁾	ST	2.99E-08	NA
	Cary	0.90 mi @ 83°E	RX	2.07E-07	NA
	Location No. 78	0.90 mi @ 83°E	TB	1.88E-07	NA
		0.90 mi @ 83°E	RF	2.07E-07	NA
		0.90 mi @ 83°E	RW	3.06E-07	NA
	b. Deposition ⁽³⁾	0.71 mi @ 118°ESE	ST	NA	1.60E-09
	Whaley	0.71 mi @ 118°ESE	RX	NA	5.52E-09
	Location No. 199	0.71 mi @ 118°ESE	TB	NA	5.30E-09
		0.71 mi @ 118°ESE	RF	NA	5.52E-09
		0.71 mi @ 118°ESE	RW	NA	6.28E-09
B.	NOBLE GASES				
1.	Air Dose	1.55 mi @ 90°E ⁽¹⁾	ST	2.99E-08	NA
	Annual Average	0.60 mi @ 90°E	ST(fc)	1.16E-07	NA
	Site Boundary	0.60 mi @ 90°E	RX	3.58E-07	NA
		0.60 mi @ 90°E	TB	3.19E-07	NA
		0.60 mi @ 90°E	RF	3.58E-07	NA
		0.60 mi @ 90°E	RW	5.39E-07	NA
2.	Total Body	0.60 mi @ 90°E	ST(fc)	1.16E-07	NA
	Annual Average	0.60 mi @ 90°E	RX	3.58E-07	NA
	Site Boundary	0.60 mi @ 90°E	TB	3.19E-07	NA
		0.60 mi @ 90°E	RF	3.58E-07	NA
		0.60 mi @ 90°E	RW	5.39E-07	NA

ADDENDUM 1 (continued)

TABLE 2 METEOROLOGICAL DATA AND LOCATIONS OF INTEREST

RECEPTOR	GEOGRAPHIC LOCATION	D	ATMOS ISPERSION	PHERIC** I FACTOR
B. NOBLE GAS (continued)	ES DISTANCE/ DIRECTION	RELEASE POINT	X/Q (sec/m3)	D/Q (1/m2)
3. Skin	1.55 mi @ 90°E	ST	2.99E-08	NA
Annual Average Site Boundary	e 0.60 mi @ 90°E 0.60 mi @ 90°E 0.60 mi @ 90°E	ST(fc) RX TB	1.16E-07 3.58E-07 3.19E-07	NA NA NA
	0.60 mi @ 90°E 0.60 mi @ 90°E	RF RW	3.58E-07 5.39E-07	NA NA

* Tritium Dose Calculation

** Based on ODCM X/Q, D/Q Values Rev. 11

(1) Highest Sector Average X/Q in a populated area, not an identified residence.

(2) Inhalation uses Annual Average X/Q values. All other receptors use grazing season meteorology.

(3) Deposition uses Annual Average D/Q values. All other receptors use grazing season meteorology.

ST = Main Stack

RX = Reactor Building Vent

TB = Turbine Building Vent

RF = Refuel Floor Vent

RW = Radwaste Building Vent

fc = Finite Cloud